

ROBOTICS

# Product specification

Robot stopping distances according to  
ISO 10218-1



Trace back information:  
Workspace 24B version a10  
Checked in 2024-06-12  
Skribenta version 5.5.019

**Product specification**  
**Robot stopping distances according to ISO 10218-1**

Document ID: 3HAC048645-001

Revision: AC

The information in this manual is subject to change without notice and should not be construed as a commitment by ABB. ABB assumes no responsibility for any errors that may appear in this manual.

Except as may be expressly stated anywhere in this manual, nothing herein shall be construed as any kind of guarantee or warranty by ABB for losses, damage to persons or property, fitness for a specific purpose or the like.

In no event shall ABB be liable for incidental or consequential damages arising from use of this manual and products described herein.

This manual and parts thereof must not be reproduced or copied without ABB's written permission.

Keep for future reference.

Additional copies of this manual may be obtained from ABB.

Original instructions.

© Copyright 2013-2024 ABB. All rights reserved.  
Specifications subject to change without notice.

# Table of contents

Overview of this specification .....	9
<b>1 About the data</b>	<b>13</b>
<b>2 Measuring stopping distance and time</b>	<b>17</b>
<b>3 IRB 1200</b>	<b>19</b>
3.1 IRB 1200 0.7 m 7 kg .....	19
3.2 IRB 1200 0.7 m 7 kg .....	28
3.3 IRB 1200 0.9 m 5 kg .....	37
3.4 IRB 1200 0.9 m 5 kg .....	46
<b>4 IRB 1510</b>	<b>55</b>
4.1 IRB 1510ID 1.5 m 4 kg .....	55
<b>5 IRB 1520</b>	<b>65</b>
5.1 IRB 1520ID 1.5 m 4 kg .....	65
<b>6 IRB 1600</b>	<b>75</b>
6.1 IRB 1600 1.2 m 6 kg .....	75
6.2 IRB 1600 1.2 m 10 kg .....	84
6.3 IRB 1600 1.45 m 6 kg .....	93
6.4 IRB 1600 1.45 m 10 kg .....	102
6.5 IRB 1600ID 1.5 m 4 kg .....	111
<b>7 IRB 1660</b>	<b>121</b>
7.1 IRB 1660ID 1.55 m 4 kg .....	121
7.2 IRB 1660ID 1.55 m 6 kg .....	130
<b>8 IRB 2400</b>	<b>139</b>
8.1 IRB 2400 1.5 m 10 kg .....	139
8.2 IRB 2400 1.5 m 16 kg .....	148
<b>9 IRB 2600</b>	<b>157</b>
9.1 IRB 2600 1.65 m 12 kg .....	157
9.2 IRB 2600 1.65 m 20 kg .....	166
9.3 IRB 2600 1.85 m 12 kg .....	175
9.4 IRB 2600ID 1.85 m 15 kg .....	184
9.5 IRB 2600ID 2.00 m 8 kg .....	193
<b>10 IRB 4400</b>	<b>203</b>
10.1 IRB 4400 1.95 m 45 kg .....	203
10.2 IRB 4400 1.95 m 60 kg .....	212
10.3 IRB 4400 2.6 m 10 kg .....	221
<b>11 IRB 4600</b>	<b>231</b>
11.1 IRB 4600 2.05 m 45 kg .....	231
11.2 IRB 4600 2.05 m 60 kg .....	240
11.3 IRB 4600 2.50 m 20 kg .....	249
11.4 IRB 4600 2.55 m 40 kg .....	258
<b>12 IRB 6620</b>	<b>267</b>
12.1 IRB 6620 2.20 m 150 kg .....	267

## Table of contents

---

<b>13 IRB 6650</b>	<b>277</b>
13.1 IRB 6650S 3.00 m 200 kg .....	277
13.2 IRB 6650S 3.45 m 125 kg .....	286
13.3 IRB 6650S 3.90 m 90 kg .....	295
13.4 IRB 6650SLeanID 3.0 m 190 kg .....	304
13.5 IRB 6650SLeanID 3.5 m 100 kg .....	313
<b>14 IRB 6660</b>	<b>323</b>
14.1 IRB 6660 1.90 m 205 kg .....	323
14.2 IRB 6660 3.10 m 130 kg .....	332
14.3 IRB 6660 3.35 m 100 kg .....	341
<b>15 IRB 6700</b>	<b>351</b>
15.1 IRB 6700 2.60 m 200 kg .....	351
15.2 IRB 6700 2.65 m 235 kg .....	360
15.3 IRB 6700 2.70 m 300 kg .....	369
15.4 IRB 6700 2.80 m 205 kg .....	378
15.5 IRB 6700 2.85 m 155 kg .....	387
15.6 IRB 6700 3.00 m 245 kg .....	396
15.7 IRB 6700 3.05 m 175 kg .....	405
15.8 IRB 6700 3.20 m 150 kg .....	414
15.9 IRB 6700Inv LeanID m 2.60 kg .....	423
15.10 IRB 6700Inv LeanID m 2.90 kg .....	432
15.11 IRB 6700Inv 2.60 m 300 kg .....	441
15.12 IRB 6700Inv 2.90 m 245 kg .....	450
15.13 IRB 6700LeanID 2.60 m 175 kg .....	459
15.14 IRB 6700LeanID 2.65 m 220 kg .....	468
15.15 IRB 6700LeanID 2.70 m 270 kg .....	477
15.16 IRB 6700LeanID 2.80 m 200 kg .....	486
15.17 IRB 6700LeanID 2.85 m 140 kg .....	495
15.18 IRB 6700LeanID 3.00 m 220 kg .....	504
15.19 IRB 6700LeanID 3.05 m 155 kg .....	513
15.20 IRB 6700LeanID 3.20 m 145 kg .....	522
<b>16 IRB 6790</b>	<b>531</b>
16.1 IRB 6790 2.65 m 235 kg .....	531
16.2 IRB 6790 2.80 m 205 kg .....	540
<b>17 IRB 7600</b>	<b>549</b>
17.1 IRB 7600 2.55 m 400 kg .....	549
17.2 IRB 7600 2.55 m 500 kg .....	558
17.3 IRB 7600 2.80 m 340 kg .....	567
17.4 IRB 7600 3.05 m 325 kg .....	576
17.5 IRB 7600 3.50 m 150 kg .....	585
17.6 IRB 7600LeanID 2.55 m 390 kg .....	594
17.7 IRB 7600LeanID 2.8 m 320 kg .....	603
17.8 IRB 7600LeanID 3.1 m 290 kg .....	612
<b>18 IRB 8700</b>	<b>621</b>
18.1 IRB 8700 3.50 m 800 kg .....	621
18.2 IRB 8700 4.20 m 550 kg .....	630
18.3 IRB 8700LeanID 3.50 m 630 kg .....	639
18.4 IRB 8700LeanID 4.20 m 475 kg .....	648
<b>19 IRB 460</b>	<b>657</b>
19.1 IRB 460 2.4 m 110 kg .....	657

<b>20</b>	<b>IRB 660</b>	<b>667</b>
20.1	IRB 660 3.15 m 180 kg .....	667
20.2	IRB 660 3.15 m 250 kg .....	676
<b>21</b>	<b>IRB 760</b>	<b>685</b>
21.1	IRB 760 3.2 m 445 kg .....	685
21.2	IRB 760 3.2 m 450 kg .....	694
<b>22</b>	<b>IRB 360</b>	<b>703</b>
22.1	IRB 360 0.8 m 1 kg .....	703
22.2	IRB 360 1.13 m 1 kg .....	707
22.3	IRB 360 1.13 m 3 kg .....	712
22.4	IRB 360 1.13 m 8 kg .....	717
22.5	IRB 360 1.6 m 1 kg .....	719
22.6	IRB 360 1.6 m 6 kg .....	721
<b>23</b>	<b>IRB 365</b>	<b>723</b>
23.1	IRB 365 0.8 m 1.5 kg .....	723
23.2	IRB 365 1.1 m 1.5 kg .....	725
23.3	IRB 365 1.3 m 1.5 kg .....	727
<b>24</b>	<b>IRB 390</b>	<b>729</b>
24.1	IRB 390 1.3 m 10 kg .....	729
24.2	IRB 390 1.3 m 15 kg .....	731
<b>25</b>	<b>IRBP A</b>	<b>733</b>
25.1	A250_D1000 .....	733
25.2	A500_D1000 .....	737
25.3	A500_D1450 .....	741
25.4	A750_D1000 .....	745
25.5	A750_D1450 .....	749
<b>26</b>	<b>IRBP B</b>	<b>753</b>
26.1	B250_D1000 .....	753
26.2	B500_D1450 .....	759
26.3	B750_D1450 .....	765
<b>27</b>	<b>IRBP C</b>	<b>771</b>
27.1	C500 .....	771
27.2	C1000 .....	773
<b>28</b>	<b>IRBP D</b>	<b>775</b>
28.1	D300_L1250_D1000 .....	775
28.2	D300_L1600_D1000 .....	781
28.3	D600_L1600_D1000 .....	787
28.4	D600_L1600_D1200 .....	793
28.5	D600_L2000_D1000 .....	799
28.6	D600_L2000_D1200 .....	805
<b>29</b>	<b>IRBP K</b>	<b>811</b>
29.1	K1000_D1200 .....	811
29.2	K1000_D1400 .....	815
29.3	K300_D1000 .....	819
29.4	K300_D1200 .....	823
29.5	K600_D1200 .....	827
29.6	K600_D1400 .....	831

## Table of contents

---

<b>30 IRBP L</b>	<b>835</b>
30.1 L1000 .....	835
30.2 L2000 .....	837
30.3 L300 .....	839
30.4 L5000 .....	841
30.5 L600 .....	843
<b>31 IRBP R</b>	<b>845</b>
31.1 R1000_L1600_D1000 .....	845
31.2 R1000_L1600_D1200 .....	849
31.3 R1000_L2000_D1000 .....	853
31.4 R1000_L2000_D1200 .....	857
31.5 R300_L1250_D1000 .....	861
31.6 R300_L1600_D1000 .....	865
31.7 R600_L1600_D1000 .....	869
31.8 R600_L1600_D1200 .....	873
31.9 R600_L2000_D1000 .....	877
31.10 R600_L2000_D1200 .....	881
<b>Index</b>	<b>885</b>

---



# Overview of this specification

## About this specification

This specification contains stopping distances and times for category 0 and category 1 stops, as required by EN ISO 10218-1 Annex B.

## Usage

This specification should be used when calculating the safe distance in applying safeguarding devices.

## Who should read this manual?

This specification is intended for:

- Personnel working with planning of robot systems

## References

Documentation referred to in the manual, is listed in the table below.

Document name	Document ID
<i>Safety manual for robot - Manipulator and IRC5 or OmniCore controller</i> <sup>i</sup>	3HAC031045-001
Product specifications for the respective robots	
Standard: <i>EN ISO 10218-1, Annex B</i>	

<sup>i</sup> This manual contains all safety instructions from the product manuals for the manipulators and the controllers.




## Revisions

Revision	Description
-	First edition. Release 13.2.
A	Release 14.1. The following robots are added: <ul style="list-style-type: none"> <li>• IRB 120</li> <li>• IRB 140</li> <li>• IRB 6700</li> <li>• IRB 260</li> <li>• IRB 460</li> <li>• IRB 660</li> <li>• IRB 760</li> </ul>
B	Release 15.1. The following robots are added: <ul style="list-style-type: none"> <li>• IRB 6700 variants</li> <li>• IRB 1200</li> <li>• IRB 1520</li> <li>• IRB 1600</li> </ul> Descriptions about the data and measurements are updated.
C	Release 15.2. The following robots are added: <ul style="list-style-type: none"> <li>• IRB 2400</li> </ul>

*Continues on next page*

## Overview of this specification

Continued

Revision	Description
	<ul style="list-style-type: none"> <li>IRB 4400</li> <li>IRB 8700</li> </ul>  <b>Note</b> Category 0 values are missing for IRB 7600 2.80 m 340 kg.
D	Release 16.1. The following robots are added: <ul style="list-style-type: none"> <li>New variants for IRB 1600ID</li> </ul> This revision includes the following additions and/or changes: <ul style="list-style-type: none"> <li>A description of how to measure the stopping distance and time for your installation is added, see <a href="#">Measuring stopping distance and time on page 17</a>.</li> </ul>
E	Release 16.1. <ul style="list-style-type: none"> <li>Rename of the new variant IRB 1600ID - 6/1.55 to IRB 1660ID - 6/1.55.</li> <li>Re-inserted IRB 1600ID-4/1.5 that was missing in the previous revision.</li> </ul>
F	Release 16.2. <ul style="list-style-type: none"> <li>Improved measurements for 4-axis articulated robots.</li> <li>Category 0 values are added for IRB 7600 340/2.80.</li> </ul>
G	Release 17.2. <ul style="list-style-type: none"> <li>Updated data for all previously published robots.</li> <li>Added information about naming conventions, see <a href="#">Naming of product variants in this document on page 15</a>.</li> <li>The following robots are added:               <ul style="list-style-type: none"> <li>IRB 360</li> </ul> </li> </ul>  <b>Note</b> For stop category 0, the robot may hit the mechanical stops before the speed is reduced to 0. <ul style="list-style-type: none"> <li>IRB 6700Inv</li> </ul>
H	Release 19A. The following robots are added: <ul style="list-style-type: none"> <li>IRB 6790</li> <li>IRBP K, IRBP L, IRB R</li> </ul>  <b>Note</b> Data for IRBP C will be added in a later release.
J	The following robots are added: <ul style="list-style-type: none"> <li>IRB 910SC</li> </ul>
K	The following robots are added: <ul style="list-style-type: none"> <li>IRBP A, IRBP B, IRBP D</li> <li>Corrected names in tables for IRBP R.</li> </ul>
L	The following robots are added: <ul style="list-style-type: none"> <li>IRB 910INV</li> <li>IRB 1100</li> <li>IRBP C</li> </ul>
M	Added back IRB 2600, that was accidentally removed from revision L.

Continues on next page

Revision	Description
N	Added correct graphics for IRB 2600. The graphics used in revisions J to M are not correct.
P	Release 20C. The category 0 stop data for all IRBP is updated with graphics. The following robots are added: <ul style="list-style-type: none"> <li>• IRB 1300</li> </ul>
Q	Release 20C. The following robots are added: <ul style="list-style-type: none"> <li>• IRB 760, 445 kg variant</li> </ul> The description about measurement and calculation is updated.
R	Release 21A. The following robots are added: <ul style="list-style-type: none"> <li>• IRB 390</li> </ul>
S	Release 21B. The following robots are added: <ul style="list-style-type: none"> <li>• CRB 1100</li> <li>• CRB 15000</li> </ul>
T	Release 21C. The following robots are added: <ul style="list-style-type: none"> <li>• IRB 920</li> </ul> The graphs for IRB 1660ID are corrected.
U	Release 22A. The following robots are added: <ul style="list-style-type: none"> <li>• IRB 1300-12/1.4</li> <li>• IRB 5710</li> <li>• IRB 5720</li> </ul> The robot IRB 260 is removed as it is phased out from the official product offer.
V	Release 22B. The following robots are added: <ul style="list-style-type: none"> <li>• IRB 365</li> </ul>
W	Release 22C. The following robots are added: <ul style="list-style-type: none"> <li>• IRB 1010</li> <li>• IRB 920, new variants</li> </ul>
X	Release 22D. The following robots are added: <ul style="list-style-type: none"> <li>• CRB 1300</li> </ul>
Y	Release 23A. <ul style="list-style-type: none"> <li>• IRB 365, new variants</li> <li>• The robot IRB 140 is removed as it is phased out from the official product offer.</li> <li>• The robot IRB 6640 is removed as it is phased out from the official product offer.</li> </ul>
Z	Release 23B. <ul style="list-style-type: none"> <li>• The data for the CRB 15000 and IRB 5710/5720 robots is moved to their respective product specification. All documents are available on <a href="http://www.abb.com/robotics">www.abb.com/robotics</a>.</li> </ul> The data for new robots is included in their respective product specification.

Continues on next page

## Overview of this specification

---

Continued

Revision	Description
	<ul style="list-style-type: none"><li>Removed duplicated pages for IRB 1010.</li></ul>
AA	<p>Release 23C.</p> <p>The following robots are added:</p> <ul style="list-style-type: none"><li>IRB 1510</li></ul> <p>The data for the CRB 1100, CRB 1300, IRB 1010, IRB 1100, IRB 1300, IRB 910INV, and IRB 920 robots is moved to their respective product specification. All documents are available on <a href="http://www.abb.com/robotics">www.abb.com/robotics</a>.</p> <p>The data for new robots is included in their respective product specification.</p>
AB	<p>Release 24A.</p> <ul style="list-style-type: none"><li>Corrected the category 0 stop data for IRB 1600.</li><li>IRB 120 is phased out from the product offer.</li></ul>
AC	<p>Release 24B.</p> <ul style="list-style-type: none"><li>IRB 1410 is phased out from the product offer.</li><li>IRB 910SC is phased out from the product offer.</li><li>The stopping data for IRB 1200 OmniCore robots is moved to <i>Product specification - IRB 1200, 3HAC081417-001</i>.</li></ul>

# 1 About the data

## Robot stopping distances and times

For articulated and SCARA robots, all measurements and calculations of stopping distances and times are done according to ISO 10218-1, with single axis motion on axes 1, 2, and 3. If more than one axis is used for the movement, then the stopping distance and time can be longer. Normal delays of the hardware and software are taken into account.

For delta robots (parallel arm) the values are based on movement by all axes, as these axes always move together. Only stopping times are presented.

For positioners the values are based on single axis movement.

The stop categories 0 and 1 are according to IEC 60204-1.

## Category 0 stops

The stopping distance and time for category 0 stops are simulated using maximum speed, maximum payload, and the arm stretched out to the maximum reach.



### Note

For SCARA robots without brakes on axis 1 and 2, the stopping distances for category 0 stops in actual applications can be longer than those stated in this document because without brakes, it is the friction that will stop the robot (on axes without brakes).

## Category 1 stops

The stop category 1 data are based on calculations in simulation of worst case scenarios. The data for stop category 1 are verified by measurements.

The simulations and verifications are done with the default value (100%) for the system parameter *AccSet*. Changing this value will affect the stopping distances and times (only for robots running on versions prior to RobotWare 6.01).



### Note

The stop category 1 is a controlled stop and will therefore have less deviation from the programmed path compared with a stop category 0.

## Robots

For robots the stopping distance and time for category 1 stop is provided for three arm extensions and three payloads. These variables are 100%, 66%, and 33% of the maximum values for the robot.

The speed and zone data in the simulations are based on TCP0.

## Positioners

For positioners the stopping distance and time is provided for three payloads. No extension zones are applicable. The payloads are 100%, 66%, and 33% of the maximum values for the positioner.

*Continues on next page*

# 1 About the data

Continued

Positioners with more than one station are presented with only one station data as the stations are identical.

## Loads




The used loads represent the rated load, with rated inertia in the load diagram, maximum cog z, and zero cog x and cog y. No arm load is used. The load diagrams are available in the respective product specification.

At 66% load and 33% load, the mass and inertia are reduced to 66% and 33% but cog z is the same as for 100% load.

## Extension zones for articulated robots

The extension zone for the stop category 1 is based on the wrist center point (WCP).

The extension zone limits describe the size of the respective zones. Radius R is measured from the axis-1 center.

Zone 0 (Z0)	Zone 1 (Z1)	Zone 2 (Z2)
Radius (R) is 0-33% of maximum reach of the wrist center point (WCP).	Radius (R) is 33-66% of maximum reach of the wrist center point (WCP).	Radius (R) is 66-100% of maximum reach of the wrist center point (WCP).
 xx1300002264	 xx1300002265	 xx1300002266

## Speed

For robots the TCP0 speed is measured in meters per second when the stop is triggered.

For positioners the speed is the angular speed in radians per second.

## Stopping distances

The stopping distance is measured in degrees.



### Note

The stopping distances are presented as angles. Large angles with TCP0 close to the rotation center do not necessarily correspond to a long stopping distance. Therefore a large stop angle can represent a short TCP stop distance.



### Note

The stopping distance for delta robots is measured in meters.

## Stopping times

The stopping time is measured in seconds.

Continues on next page

---

## Limitations

The stopping distance can vary depending on additional loads on the robot.

The stopping distance for category 0 stops can vary depending on the individual brakes and their friction.

This document includes the robot variants that are part of the official product offer at the time of the release of this revision.

---

## Naming of product variants in this document

The product variants presented in this document are named according to their reach and capacity. This corresponds to their official variant name but there are a few exceptions where the the names do not match due to different data sources. For example, IRB 6650S 125/3.5 is listed as IRB 6650S 3.45 m 125 kg.

**This page is intentionally left blank**



## 2 Measuring stopping distance and time

---

### Preparations before measuring

For measurement and calculation of overall system stopping performance, see ISO 13855:2010.

The measurement shall be done for the selected stop category. The emergency stop button on the robot controller is configured for stop category 0 on delivery. A risk assessment can conclude the need for another stop category. The stop category can be changed through the system parameter *Function* (topic *Controller*, type *Safety Run Chain*). In case of deviations of the default configuration of stop category 0, then this is detailed in the product specification for the respective manipulator.



#### CAUTION

The measurement and calculation of overall stopping performance for a robot must be tested with its correct load, speed, and tools, in its actual environment, before the robot is taken into production.

All load and tool data must be correctly defined (weight, CoG, moment of inertia). The load identification service routine can be used to identify the data.



#### CAUTION

Follow the safety instructions in the respective product manual for the robot.

### Measuring with TuneMaster

The software TuneMaster can be used to measure stopping distances and times for ABB robots. The TuneMaster software contains documentation on how to use it.


- 1 Download TuneMaster from [www.abb.com/robotics](http://www.abb.com/robotics), section **RobotStudio - Downloads - RobotWare Tools and Utilities**.
- 2 Install TuneMaster on a computer. Start the TuneMaster app and select **Log Signals**.
- 3 Connect to the robot controller.
- 4 Define the I/O stop signal to use for measurement, for example, ES1 for emergency stop.
- 5 Define the signal number to use for measurement, 1298 for axis position. The value is given in radians.
- 6 Start the logging in TuneMaster.
- 7 Start the test program on the controller.
- 8 When the axis has reached maximum speed, press the emergency stop button.
- 9 In TuneMaster, measure the stopping distance and time.
- 10 Repeat for all installed emergency stop buttons until the identified hazards due to stopping distance and time for axes have been verified.

*Continues on next page*

## 2 Measuring stopping distance and time

Continued

### Example from TuneMaster



xx160000386

## 3 IRB 1200

### 3.1 IRB 1200 0.7 m 7 kg



#### Note

This data is applicable for the IRC5 robot. For OmniCore robots, see *Product specification - IRB 1200, 3HAC081417-001*.

#### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	32.7	0.14
2	37.2	0.22
3	37.6	0.16


#### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	0.235
1	0.235	0.469
2	0.469	max reach

#### Category 1, Axis 1

Extension zone 0, stopping distance and stopping time




Continues on next page



### 3 IRB 1200

#### 3.1 IRB 1200 0.7 m 7 kg

Continued





#### Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



Continues on next page



### 3 IRB 1200

#### 3.1 IRB 1200 0.7 m 7 kg

Continued



#### Category 1, Axis 2

Extension zone 0, stopping distance and stopping time



Continues on next page

Extension zone 1, stopping distance and stopping time





Continues on next page

### 3 IRB 1200

#### 3.1 IRB 1200 0.7 m 7 kg

Continued

Extension zone 2, stopping distance and stopping time





Continues on next page



Category 1, Axis 3

Extension zone 0, stopping distance and stopping time





Continues on next page

### 3 IRB 1200

#### 3.1 IRB 1200 0.7 m 7 kg



Continued

Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



### 3 IRB 1200

#### 3.2 IRB 1200 0.7 m 7 kg

#### 3.2 IRB 1200 0.7 m 7 kg



#### Note

This data is applicable for the IRC5 robot. For OmniCore robots, see *Product specification - IRB 1200, 3HAC081417-001*.

#### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	32.7	0.14
2	37.1	0.22
3	37.6	0.16


#### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).


Zone	wcp min (m)	wcp max (m)
0	0	0.235
1	0.235	0.469
2	0.469	max reach

#### Category 1, Axis 1



Extension zone 0, stopping distance and stopping time



Continues on next page



Extension zone 1, stopping distance and stopping time





Continues on next page

### 3 IRB 1200

#### 3.2 IRB 1200 0.7 m 7 kg

Continued



#### Extension zone 2, stopping distance and stopping time



Continues on next page

Category 1, Axis 2

Extension zone 0, stopping distance and stopping time





Continues on next page

### 3 IRB 1200

#### 3.2 IRB 1200 0.7 m 7 kg

Continued



#### Extension zone 1, stopping distance and stopping time



Continues on next page



Extension zone 2, stopping distance and stopping time



Continues on next page



### 3 IRB 1200

3.2 IRB 1200 0.7 m 7 kg

Continued



#### Category 1, Axis 3

Extension zone 0, stopping distance and stopping time



Continues on next page

Extension zone 1, stopping distance and stopping time





Continues on next page

### 3 IRB 1200

#### 3.2 IRB 1200 0.7 m 7 kg

Continued

Extension zone 2, stopping distance and stopping time



## 3.3 IRB 1200 0.9 m 5 kg

**Note**

This data is applicable for the IRC5 robot. For OmniCore robots, see *Product specification - IRB 1200, 3HAC081417-001*.

**Category 0**

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	39.1	0.19
2	45.8	0.29
3	42.1	0.2


**Category 1, extension zones**

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	0.3
1	0.3	0.601
2	0.601	max reach

**Category 1, Axis 1**

Extension zone 0, stopping distance and stopping time




*Continues on next page*



### 3 IRB 1200

#### 3.3 IRB 1200 0.9 m 5 kg

Continued





#### Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



Continues on next page



### 3 IRB 1200

3.3 IRB 1200 0.9 m 5 kg

Continued

#### Category 1, Axis 2



Extension zone 0, stopping distance and stopping time



Continues on next page



Extension zone 1, stopping distance and stopping time





Continues on next page

### 3 IRB 1200

#### 3.3 IRB 1200 0.9 m 5 kg

Continued



Extension zone 2, stopping distance and stopping time



Continues on next page

Category 1, Axis 3

Extension zone 0, stopping distance and stopping time





Continues on next page

### 3 IRB 1200

#### 3.3 IRB 1200 0.9 m 5 kg



Continued

#### Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



### 3 IRB 1200

#### 3.4 IRB 1200 0.9 m 5 kg

#### 3.4 IRB 1200 0.9 m 5 kg



#### Note

This data is applicable for the IRC5 robot. For OmniCore robots, see *Product specification - IRB 1200, 3HAC081417-001*.

#### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	39.1	0.19
2	45.6	0.29
3	41.9	0.2


#### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).


Zone	wcp min (m)	wcp max (m)
0	0	0.3
1	0.3	0.601
2	0.601	max reach

#### Category 1, Axis 1



Extension zone 0, stopping distance and stopping time



Continues on next page



Extension zone 1, stopping distance and stopping time





Continues on next page

### 3 IRB 1200

#### 3.4 IRB 1200 0.9 m 5 kg

Continued

Extension zone 2, stopping distance and stopping time





Continues on next page



## Category 1, Axis 2

Extension zone 0, stopping distance and stopping time





Continues on next page

### 3 IRB 1200

#### 3.4 IRB 1200 0.9 m 5 kg



Continued

#### Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



Continues on next page



### 3 IRB 1200

3.4 IRB 1200 0.9 m 5 kg

Continued



#### Category 1, Axis 3

Extension zone 0, stopping distance and stopping time



Continues on next page

Extension zone 1, stopping distance and stopping time





Continues on next page

### 3 IRB 1200

#### 3.4 IRB 1200 0.9 m 5 kg

Continued

#### Extension zone 2, stopping distance and stopping time



## 4 IRB 1510

### 4.1 IRB 1510ID 1.5 m 4 kg

#### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	20.2	0.22
2	18.5	0.17
3	15.0	0.12


#### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	0.5
1	0.5	1.0
2	1.0	max reach

#### Category 1, Axis 1

Extension zone 0, stopping distance and stopping time




*Continues on next page*



## 4 IRB 1510

### 4.1 IRB 1510ID 1.5 m 4 kg

Continued





Extension zone 1, stopping distance and stopping time



Continues on next page



Extension zone 2, stopping distance and stopping time



Continues on next page



## 4 IRB 1510

### 4.1 IRB 1510ID 1.5 m 4 kg

Continued



#### Category 1, Axis 2

Extension zone 0, stopping distance and stopping time



Continues on next page

Extension zone 1, stopping distance and stopping time





Continues on next page

## 4 IRB 1510

### 4.1 IRB 1510ID 1.5 m 4 kg

Continued



Extension zone 2, stopping distance and stopping time



Continues on next page

## Category 1, Axis 3

## Extension zone 0, stopping distance and stopping time





Continues on next page

## 4 IRB 1510

### 4.1 IRB 1510ID 1.5 m 4 kg



Continued

Extension zone 1, stopping distance and stopping time



Continues on next page

## Extension zone 2, stopping distance and stopping time



**This page is intentionally left blank**



## 5 IRB 1520

### 5.1 IRB 1520ID 1.5 m 4 kg

#### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	20.2	0.22
2	18.5	0.17
3	15.0	0.12


#### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	0.5
1	0.5	1.0
2	1.0	max reach

#### Category 1, Axis 1

Extension zone 0, stopping distance and stopping time




*Continues on next page*



## 5 IRB 1520

### 5.1 IRB 1520ID 1.5 m 4 kg

Continued





#### Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



Continues on next page



## 5 IRB 1520

### 5.1 IRB 1520ID 1.5 m 4 kg

Continued



#### Category 1, Axis 2

Extension zone 0, stopping distance and stopping time



Continues on next page

Extension zone 1, stopping distance and stopping time





Continues on next page

## 5 IRB 1520

### 5.1 IRB 1520ID 1.5 m 4 kg

Continued



Extension zone 2, stopping distance and stopping time



Continues on next page

## Category 1, Axis 3

## Extension zone 0, stopping distance and stopping time





Continues on next page

## 5 IRB 1520

### 5.1 IRB 1520ID 1.5 m 4 kg

Continued



Extension zone 1, stopping distance and stopping time



Continues on next page



## Extension zone 2, stopping distance and stopping time



**This page is intentionally left blank**

## 6 IRB 1600

### 6.1 IRB 1600 1.2 m 6 kg

#### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	19.7	0.17
2	16.8	0.12
3	16.1	0.1


#### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	0.408
1	0.408	0.817
2	0.817	max reach

#### Category 1, Axis 1

Extension zone 0, stopping distance and stopping time




*Continues on next page*



## 6 IRB 1600

### 6.1 IRB 1600 1.2 m 6 kg

Continued





#### Extension zone 1, stopping distance and stopping time



Continues on next page

## Extension zone 2, stopping distance and stopping time



Continues on next page



## 6 IRB 1600

6.1 IRB 1600 1.2 m 6 kg

Continued



### Category 1, Axis 2

Extension zone 0, stopping distance and stopping time



Continues on next page

## Extension zone 1, stopping distance and stopping time





Continues on next page

## 6 IRB 1600

### 6.1 IRB 1600 1.2 m 6 kg

Continued

Extension zone 2, stopping distance and stopping time





Continues on next page



## Category 1, Axis 3

Extension zone 0, stopping distance and stopping time





Continues on next page

## 6 IRB 1600

### 6.1 IRB 1600 1.2 m 6 kg



Continued

#### Extension zone 1, stopping distance and stopping time



Continues on next page

## Extension zone 2, stopping distance and stopping time



## 6 IRB 1600

### 6.2 IRB 1600 1.2 m 10 kg

### 6.2 IRB 1600 1.2 m 10 kg

#### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	22.7	0.17
2	26.1	0.2
3	22.3	0.15


#### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).


Zone	wcp min (m)	wcp max (m)
0	0	0.408
1	0.408	0.817
2	0.817	max reach

#### Category 1, Axis 1



Extension zone 0, stopping distance and stopping time



Continues on next page



Extension zone 1, stopping distance and stopping time





Continues on next page

## 6 IRB 1600

### 6.2 IRB 1600 1.2 m 10 kg

Continued



Extension zone 2, stopping distance and stopping time



Continues on next page

## Category 1, Axis 2

## Extension zone 0, stopping distance and stopping time





Continues on next page

## 6 IRB 1600

### 6.2 IRB 1600 1.2 m 10 kg

Continued



Extension zone 1, stopping distance and stopping time



Continues on next page



## Extension zone 2, stopping distance and stopping time



Continues on next page



## 6 IRB 1600

### 6.2 IRB 1600 1.2 m 10 kg

Continued



#### Category 1, Axis 3

Extension zone 0, stopping distance and stopping time



Continues on next page

## Extension zone 1, stopping distance and stopping time





Continues on next page

## 6 IRB 1600

### 6.2 IRB 1600 1.2 m 10 kg

Continued

Extension zone 2, stopping distance and stopping time



## 6.3 IRB 1600 1.45 m 6 kg

### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	23.4	0.2
2	22.0	0.17
3	15.8	0.1


### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	0.483
1	0.483	0.967
2	0.967	max reach

### Category 1, Axis 1

Extension zone 0, stopping distance and stopping time




*Continues on next page*



## 6 IRB 1600

### 6.3 IRB 1600 1.45 m 6 kg

Continued





#### Extension zone 1, stopping distance and stopping time



Continues on next page

## Extension zone 2, stopping distance and stopping time



Continues on next page



## 6 IRB 1600

6.3 IRB 1600 1.45 m 6 kg

Continued

### Category 1, Axis 2



Extension zone 0, stopping distance and stopping time



Continues on next page



## Extension zone 1, stopping distance and stopping time





Continues on next page

## 6 IRB 1600

### 6.3 IRB 1600 1.45 m 6 kg

Continued



#### Extension zone 2, stopping distance and stopping time



Continues on next page

## Category 1, Axis 3

## Extension zone 0, stopping distance and stopping time





Continues on next page

## 6 IRB 1600

### 6.3 IRB 1600 1.45 m 6 kg



Continued

#### Extension zone 1, stopping distance and stopping time



Continues on next page

## Extension zone 2, stopping distance and stopping time



## 6 IRB 1600

### 6.4 IRB 1600 1.45 m 10 kg

### 6.4 IRB 1600 1.45 m 10 kg

#### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	33.1	0.28
2	38.5	0.34
3	29.4	0.22


#### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).


Zone	wcp min (m)	wcp max (m)
0	0	0.483
1	0.483	0.967
2	0.967	max reach

#### Category 1, Axis 1



Extension zone 0, stopping distance and stopping time



Continues on next page



Extension zone 1, stopping distance and stopping time





Continues on next page

## 6 IRB 1600

### 6.4 IRB 1600 1.45 m 10 kg

Continued

Extension zone 2, stopping distance and stopping time





Continues on next page



## Category 1, Axis 2

Extension zone 0, stopping distance and stopping time





Continues on next page

## 6 IRB 1600

### 6.4 IRB 1600 1.45 m 10 kg



Continued

#### Extension zone 1, stopping distance and stopping time



Continues on next page

## Extension zone 2, stopping distance and stopping time



Continues on next page



## 6 IRB 1600

6.4 IRB 1600 1.45 m 10 kg

Continued



### Category 1, Axis 3

Extension zone 0, stopping distance and stopping time



Continues on next page

## Extension zone 1, stopping distance and stopping time





Continues on next page

## 6 IRB 1600

### 6.4 IRB 1600 1.45 m 10 kg

Continued

#### Extension zone 2, stopping distance and stopping time



## 6.5 IRB 1600ID 1.5 m 4 kg

### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	32.2	0.25
2	29.1	0.22
3	21.5	0.15


### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	0.5
1	0.5	1.0
2	1.0	max reach

### Category 1, Axis 1

Extension zone 0, stopping distance and stopping time




*Continues on next page*



## 6 IRB 1600

6.5 IRB 1600ID 1.5 m 4 kg

Continued





Extension zone 1, stopping distance and stopping time



Continues on next page



## Extension zone 2, stopping distance and stopping time



Continues on next page



## 6 IRB 1600

6.5 IRB 1600ID 1.5 m 4 kg

Continued



### Category 1, Axis 2

Extension zone 0, stopping distance and stopping time



Continues on next page

## Extension zone 1, stopping distance and stopping time





Continues on next page

## 6 IRB 1600

### 6.5 IRB 1600ID 1.5 m 4 kg

Continued



Extension zone 2, stopping distance and stopping time



Continues on next page

## Category 1, Axis 3

Extension zone 0, stopping distance and stopping time





Continues on next page

## 6 IRB 1600

6.5 IRB 1600ID 1.5 m 4 kg



Continued

Extension zone 1, stopping distance and stopping time



Continues on next page

## Extension zone 2, stopping distance and stopping time



**This page is intentionally left blank**



## 7 IRB 1660

### 7.1 IRB 1660ID 1.55 m 4 kg

#### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	29.6	0.22
2	40.2	0.34
3	26.8	0.2


#### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	0.0
1	0.0	0.0
2	0.0	max reach

#### Category 1, Axis 1

Extension zone 0, stopping distance and stopping time




*Continues on next page*



## 7 IRB 1660

7.1 IRB 1660ID 1.55 m 4 kg

Continued





Extension zone 1, stopping distance and stopping time



Continues on next page

## Extension zone 2, stopping distance and stopping time



Continues on next page



## 7 IRB 1660

7.1 IRB 1660ID 1.55 m 4 kg

Continued



### Category 1, Axis 2

Extension zone 0, stopping distance and stopping time



Continues on next page

## Extension zone 1, stopping distance and stopping time





Continues on next page

## 7 IRB 1660

7.1 IRB 1660ID 1.55 m 4 kg

Continued



Extension zone 2, stopping distance and stopping time



Continues on next page

## Category 1, Axis 3

Extension zone 0, stopping distance and stopping time





Continues on next page

## 7 IRB 1660

7.1 IRB 1660ID 1.55 m 4 kg

Continued



Extension zone 1, stopping distance and stopping time



Continues on next page



## Extension zone 2, stopping distance and stopping time



## 7 IRB 1660

### 7.2 IRB 1660ID 1.55 m 6 kg

### 7.2 IRB 1660ID 1.55 m 6 kg

#### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	29.5	0.22
2	39.5	0.32
3	26.6	0.2


#### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).


Zone	wcp min (m)	wcp max (m)
0	0	0.0
1	0.0	0.0
2	0.0	max reach

#### Category 1, Axis 1



Extension zone 0, stopping distance and stopping time



Continues on next page



Extension zone 1, stopping distance and stopping time





Continues on next page

## 7 IRB 1660

7.2 IRB 1660ID 1.55 m 6 kg

Continued



Extension zone 2, stopping distance and stopping time



Continues on next page

## Category 1, Axis 2

## Extension zone 0, stopping distance and stopping time





Continues on next page

## 7 IRB 1660

7.2 IRB 1660ID 1.55 m 6 kg



Continued

Extension zone 1, stopping distance and stopping time



Continues on next page

## Extension zone 2, stopping distance and stopping time



Continues on next page



## 7 IRB 1660

7.2 IRB 1660ID 1.55 m 6 kg

Continued

### Category 1, Axis 3



Extension zone 0, stopping distance and stopping time



Continues on next page



## Extension zone 1, stopping distance and stopping time





Continues on next page

## 7 IRB 1660

7.2 IRB 1660ID 1.55 m 6 kg

Continued

Extension zone 2, stopping distance and stopping time



## 8 IRB 2400

### 8.1 IRB 2400 1.5 m 10 kg

#### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	46.9	0.51
2	36.4	0.32
3	22.8	0.2


#### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	0.524
1	0.524	1.048
2	1.048	max reach

#### Category 1, Axis 1

Extension zone 0, stopping distance and stopping time




*Continues on next page*



## 8 IRB 2400

### 8.1 IRB 2400 1.5 m 10 kg

Continued





#### Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



Continues on next page



## 8 IRB 2400

### 8.1 IRB 2400 1.5 m 10 kg

Continued



#### Category 1, Axis 2

Extension zone 0, stopping distance and stopping time



Continues on next page

## Extension zone 1, stopping distance and stopping time





Continues on next page

## 8 IRB 2400

### 8.1 IRB 2400 1.5 m 10 kg

Continued

#### Extension zone 2, stopping distance and stopping time





Continues on next page



## Category 1, Axis 3

Extension zone 0, stopping distance and stopping time





Continues on next page

## 8 IRB 2400

### 8.1 IRB 2400 1.5 m 10 kg



Continued

Extension zone 1, stopping distance and stopping time



Continues on next page

## Extension zone 2, stopping distance and stopping time



## 8 IRB 2400

### 8.2 IRB 2400 1.5 m 16 kg

### 8.2 IRB 2400 1.5 m 16 kg

#### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	53.2	0.61
2	36.1	0.32
3	29.1	0.27


#### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).


Zone	wcp min (m)	wcp max (m)
0	0	0.524
1	0.524	1.048
2	1.048	max reach

#### Category 1, Axis 1



Extension zone 0, stopping distance and stopping time



Continues on next page



Extension zone 1, stopping distance and stopping time





Continues on next page

## 8 IRB 2400

### 8.2 IRB 2400 1.5 m 16 kg

Continued



Extension zone 2, stopping distance and stopping time



Continues on next page

## Category 1, Axis 2

Extension zone 0, stopping distance and stopping time





Continues on next page

## 8 IRB 2400

### 8.2 IRB 2400 1.5 m 16 kg

Continued



Extension zone 1, stopping distance and stopping time



Continues on next page



Extension zone 2, stopping distance and stopping time



Continues on next page



## 8 IRB 2400

8.2 IRB 2400 1.5 m 16 kg

Continued



### Category 1, Axis 3

Extension zone 0, stopping distance and stopping time



Continues on next page

## Extension zone 1, stopping distance and stopping time





Continues on next page

## 8 IRB 2400

### 8.2 IRB 2400 1.5 m 16 kg

Continued

Extension zone 2, stopping distance and stopping time



## 9 IRB 2600

### 9.1 IRB 2600 1.65 m 12 kg

#### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	26.6	0.2
2	26.9	0.2
3	18.2	0.12


#### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	0.0
1	0.0	0.0
2	0.0	max reach

#### Category 1, Axis 1

Extension zone 0, stopping distance and stopping time




*Continues on next page*



## 9 IRB 2600

### 9.1 IRB 2600 1.65 m 12 kg

Continued





#### Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



Continues on next page



## 9 IRB 2600

9.1 IRB 2600 1.65 m 12 kg

Continued

### Category 1, Axis 2



Extension zone 0, stopping distance and stopping time



Continues on next page



Extension zone 1, stopping distance and stopping time





Continues on next page

## 9 IRB 2600

### 9.1 IRB 2600 1.65 m 12 kg

Continued



Extension zone 2, stopping distance and stopping time



Continues on next page

Category 1, Axis 3

Extension zone 0, stopping distance and stopping time





Continues on next page

## 9 IRB 2600

### 9.1 IRB 2600 1.65 m 12 kg



Continued

#### Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



## 9 IRB 2600

### 9.2 IRB 2600 1.65 m 20 kg

### 9.2 IRB 2600 1.65 m 20 kg

#### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	28.7	0.22
2	30.5	0.25
3	22.4	0.17


#### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).


Zone	wcp min (m)	wcp max (m)
0	0	0.0
1	0.0	0.0
2	0.0	max reach

#### Category 1, Axis 1



Extension zone 0, stopping distance and stopping time



Continues on next page



Extension zone 1, stopping distance and stopping time





Continues on next page

## 9 IRB 2600

9.2 IRB 2600 1.65 m 20 kg

Continued

Extension zone 2, stopping distance and stopping time





Continues on next page



Category 1, Axis 2

Extension zone 0, stopping distance and stopping time





Continues on next page

## 9 IRB 2600

### 9.2 IRB 2600 1.65 m 20 kg



Continued

#### Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



Continues on next page



## 9 IRB 2600

9.2 IRB 2600 1.65 m 20 kg

Continued



### Category 1, Axis 3

Extension zone 0, stopping distance and stopping time



Continues on next page

Extension zone 1, stopping distance and stopping time





Continues on next page

## 9 IRB 2600

### 9.2 IRB 2600 1.65 m 20 kg

Continued

#### Extension zone 2, stopping distance and stopping time



### 9.3 IRB 2600 1.85 m 12 kg

#### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	30.3	0.25
2	30.9	0.25
3	17.8	0.12


#### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	0.0
1	0.0	0.0
2	0.0	max reach

#### Category 1, Axis 1

Extension zone 0, stopping distance and stopping time




*Continues on next page*



## 9 IRB 2600

### 9.3 IRB 2600 1.85 m 12 kg

Continued





#### Extension zone 1, stopping distance and stopping time



Continues on next page



Extension zone 2, stopping distance and stopping time



Continues on next page



## 9 IRB 2600

9.3 IRB 2600 1.85 m 12 kg

Continued



### Category 1, Axis 2

Extension zone 0, stopping distance and stopping time



Continues on next page

Extension zone 1, stopping distance and stopping time





Continues on next page

## 9 IRB 2600

### 9.3 IRB 2600 1.85 m 12 kg

Continued



#### Extension zone 2, stopping distance and stopping time



Continues on next page

Category 1, Axis 3

Extension zone 0, stopping distance and stopping time





Continues on next page

## 9 IRB 2600

### 9.3 IRB 2600 1.85 m 12 kg



Continued

#### Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



## 9 IRB 2600

### 9.4 IRB 2600ID 1.85 m 15 kg

### 9.4 IRB 2600ID 1.85 m 15 kg

#### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	33.1	0.27
2	34.4	0.27
3	20.7	0.15


#### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	0.617
1	0.617	1.233
2	1.233	max reach


#### Category 1, Axis 1

Extension zone 0, stopping distance and stopping time





Continues on next page





Extension zone 1, stopping distance and stopping time





Continues on next page

## 9 IRB 2600

### 9.4 IRB 2600ID 1.85 m 15 kg

Continued



#### Extension zone 2, stopping distance and stopping time



Continues on next page

Category 1, Axis 2

Extension zone 0, stopping distance and stopping time





Continues on next page

## 9 IRB 2600

### 9.4 IRB 2600ID 1.85 m 15 kg



Continued

Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



Continues on next page



## 9 IRB 2600

9.4 IRB 2600ID 1.85 m 15 kg

Continued



### Category 1, Axis 3

Extension zone 0, stopping distance and stopping time



Continues on next page

Extension zone 1, stopping distance and stopping time





Continues on next page

## 9 IRB 2600

### 9.4 IRB 2600ID 1.85 m 15 kg

Continued

#### Extension zone 2, stopping distance and stopping time





## 9.5 IRB 2600ID 2.00 m 8 kg

### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	31.8	0.27
2	33.7	0.29
3	23.0	0.17


### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	0.667
1	0.667	1.333
2	1.333	max reach

### Category 1, Axis 1

Extension zone 0, stopping distance and stopping time




*Continues on next page*



## 9 IRB 2600

9.5 IRB 2600ID 2.00 m 8 kg

Continued





Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



Continues on next page



## 9 IRB 2600

9.5 IRB 2600ID 2.00 m 8 kg

Continued



### Category 1, Axis 2

Extension zone 0, stopping distance and stopping time



Continues on next page

Extension zone 1, stopping distance and stopping time





Continues on next page

## 9 IRB 2600

9.5 IRB 2600ID 2.00 m 8 kg

Continued



Extension zone 2, stopping distance and stopping time



Continues on next page

Category 1, Axis 3

Extension zone 0, stopping distance and stopping time





Continues on next page

## 9 IRB 2600

9.5 IRB 2600ID 2.00 m 8 kg

Continued



Extension zone 1, stopping distance and stopping time



Continues on next page



Extension zone 2, stopping distance and stopping time



**This page is intentionally left blank**

## 10 IRB 4400

### 10.1 IRB 4400 1.95 m 45 kg

#### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	67.8	0.8
2	18.8	0.22
3	18.2	0.22


#### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	0.661
1	0.661	1.322
2	1.322	max reach

#### Category 1, Axis 1

Extension zone 0, stopping distance and stopping time




*Continues on next page*



# 10 IRB 4400

## 10.1 IRB 4400 1.95 m 45 kg

Continued





### Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



Continues on next page



# 10 IRB 4400

10.1 IRB 4400 1.95 m 45 kg

Continued



## Category 1, Axis 2

Extension zone 0, stopping distance and stopping time



Continues on next page

Extension zone 1, stopping distance and stopping time





Continues on next page

## 10 IRB 4400

### 10.1 IRB 4400 1.95 m 45 kg

Continued

Extension zone 2, stopping distance and stopping time





Continues on next page



## Category 1, Axis 3

Extension zone 0, stopping distance and stopping time





Continues on next page

# 10 IRB 4400

10.1 IRB 4400 1.95 m 45 kg



Continued

Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



## 10 IRB 4400

10.2 IRB 4400 1.95 m 60 kg

### 10.2 IRB 4400 1.95 m 60 kg

#### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	75.1	0.9
2	20.2	0.25
3	20.6	0.27


#### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).


Zone	wcp min (m)	wcp max (m)
0	0	0.661
1	0.661	1.322
2	1.322	max reach

#### Category 1, Axis 1



Extension zone 0, stopping distance and stopping time



Continues on next page



Extension zone 1, stopping distance and stopping time





Continues on next page

# 10 IRB 4400

10.2 IRB 4400 1.95 m 60 kg

Continued



Extension zone 2, stopping distance and stopping time



Continues on next page

Category 1, Axis 2

Extension zone 0, stopping distance and stopping time





Continues on next page

# 10 IRB 4400

10.2 IRB 4400 1.95 m 60 kg

Continued



Extension zone 1, stopping distance and stopping time



Continues on next page



Extension zone 2, stopping distance and stopping time



Continues on next page



## 10 IRB 4400

10.2 IRB 4400 1.95 m 60 kg

Continued



### Category 1, Axis 3

Extension zone 0, stopping distance and stopping time



Continues on next page

Extension zone 1, stopping distance and stopping time





Continues on next page

# 10 IRB 4400

## 10.2 IRB 4400 1.95 m 60 kg

Continued

### Extension zone 2, stopping distance and stopping time



## 10.3 IRB 4400 2.6 m 10 kg

### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	51.3	0.58
2	21.1	0.2
3	19.0	0.17


### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	0.0
1	0.0	0.0
2	0.0	max reach

### Category 1, Axis 1

Extension zone 0, stopping distance and stopping time




Continues on next page



# 10 IRB 4400

## 10.3 IRB 4400 2.6 m 10 kg

Continued





### Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



Continues on next page



# 10 IRB 4400

10.3 IRB 4400 2.6 m 10 kg

Continued

## Category 1, Axis 2



Extension zone 0, stopping distance and stopping time



Continues on next page



Extension zone 1, stopping distance and stopping time





Continues on next page

## 10 IRB 4400

### 10.3 IRB 4400 2.6 m 10 kg

Continued



Extension zone 2, stopping distance and stopping time



Continues on next page

Category 1, Axis 3

Extension zone 0, stopping distance and stopping time





Continues on next page

## 10 IRB 4400

### 10.3 IRB 4400 2.6 m 10 kg



Continued

#### Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



**This page is intentionally left blank**

# 11 IRB 4600

## 11.1 IRB 4600 2.05 m 45 kg

### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	60.5	0.58
2	37.1	0.32
3	25.3	0.2


### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	0.684
1	0.684	1.367
2	1.367	max reach

### Category 1, Axis 1

Extension zone 0, stopping distance and stopping time




*Continues on next page*



# 11 IRB 4600

## 11.1 IRB 4600 2.05 m 45 kg

Continued





### Extension zone 1, stopping distance and stopping time



Continues on next page



Extension zone 2, stopping distance and stopping time



Continues on next page



# 11 IRB 4600

11.1 IRB 4600 2.05 m 45 kg

Continued



## Category 1, Axis 2

Extension zone 0, stopping distance and stopping time



Continues on next page

Extension zone 1, stopping distance and stopping time





Continues on next page

# 11 IRB 4600

## 11.1 IRB 4600 2.05 m 45 kg

Continued



### Extension zone 2, stopping distance and stopping time



Continues on next page

## Category 1, Axis 3

Extension zone 0, stopping distance and stopping time





Continues on next page

# 11 IRB 4600

## 11.1 IRB 4600 2.05 m 45 kg



Continued

### Extension zone 1, stopping distance and stopping time



Continues on next page

## Extension zone 2, stopping distance and stopping time



## 11 IRB 4600

### 11.2 IRB 4600 2.05 m 60 kg

### 11.2 IRB 4600 2.05 m 60 kg

#### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	62.9	0.66
2	40.3	0.37
3	32.8	0.27


#### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	0.684
1	0.684	1.367
2	1.367	max reach


#### Category 1, Axis 1

Extension zone 0, stopping distance and stopping time





Continues on next page





Extension zone 1, stopping distance and stopping time





Continues on next page

# 11 IRB 4600

## 11.2 IRB 4600 2.05 m 60 kg

Continued



### Extension zone 2, stopping distance and stopping time



Continues on next page

## Category 1, Axis 2

## Extension zone 0, stopping distance and stopping time





Continues on next page

# 11 IRB 4600

## 11.2 IRB 4600 2.05 m 60 kg



Continued

### Extension zone 1, stopping distance and stopping time



Continues on next page

## Extension zone 2, stopping distance and stopping time



Continues on next page



# 11 IRB 4600

11.2 IRB 4600 2.05 m 60 kg

Continued



## Category 1, Axis 3

Extension zone 0, stopping distance and stopping time



Continues on next page

## Extension zone 1, stopping distance and stopping time





Continues on next page

# 11 IRB 4600

## 11.2 IRB 4600 2.05 m 60 kg

Continued

### Extension zone 2, stopping distance and stopping time





## 11.3 IRB 4600 2.50 m 20 kg

### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	53.9	0.51
2	33.9	0.29
3	22.2	0.17


### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	0.838
1	0.838	1.675
2	1.675	max reach

### Category 1, Axis 1

Extension zone 0, stopping distance and stopping time




*Continues on next page*



# 11 IRB 4600

## 11.3 IRB 4600 2.50 m 20 kg

Continued





### Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



Continues on next page



# 11 IRB 4600

## 11.3 IRB 4600 2.50 m 20 kg

Continued



### Category 1, Axis 2

Extension zone 0, stopping distance and stopping time



Continues on next page

## Extension zone 1, stopping distance and stopping time





Continues on next page

# 11 IRB 4600

## 11.3 IRB 4600 2.50 m 20 kg

Continued



### Extension zone 2, stopping distance and stopping time



Continues on next page

## Category 1, Axis 3

## Extension zone 0, stopping distance and stopping time





Continues on next page

# 11 IRB 4600

## 11.3 IRB 4600 2.50 m 20 kg

Continued



### Extension zone 1, stopping distance and stopping time



Continues on next page



Extension zone 2, stopping distance and stopping time



## 11 IRB 4600

### 11.4 IRB 4600 2.55 m 40 kg

### 11.4 IRB 4600 2.55 m 40 kg

#### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	61.7	0.71
2	41.9	0.37
3	30.2	0.25


#### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).


Zone	wcp min (m)	wcp max (m)
0	0	0.851
1	0.851	1.701
2	1.701	max reach

#### Category 1, Axis 1



Extension zone 0, stopping distance and stopping time



Continues on next page



Extension zone 1, stopping distance and stopping time





Continues on next page

# 11 IRB 4600

## 11.4 IRB 4600 2.55 m 40 kg

Continued



### Extension zone 2, stopping distance and stopping time



Continues on next page

## Category 1, Axis 2

## Extension zone 0, stopping distance and stopping time





Continues on next page

# 11 IRB 4600

## 11.4 IRB 4600 2.55 m 40 kg



Continued

### Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



Continues on next page



# 11 IRB 4600

11.4 IRB 4600 2.55 m 40 kg

Continued

## Category 1, Axis 3



Extension zone 0, stopping distance and stopping time



Continues on next page



Extension zone 1, stopping distance and stopping time





Continues on next page

# 11 IRB 4600

## 11.4 IRB 4600 2.55 m 40 kg

Continued

### Extension zone 2, stopping distance and stopping time



## 12 IRB 6620

### 12.1 IRB 6620 2.20 m 150 kg

#### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	29.1	0.49
2	25.2	0.44
3	19.0	0.29


#### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	0.735
1	0.735	1.47
2	1.47	max reach

#### Category 1, Axis 1

Extension zone 0, stopping distance and stopping time




*Continues on next page*



## 12 IRB 6620

### 12.1 IRB 6620 2.20 m 150 kg

Continued





### Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



Continues on next page



## 12 IRB 6620

12.1 IRB 6620 2.20 m 150 kg

Continued



### Category 1, Axis 2

Extension zone 0, stopping distance and stopping time



Continues on next page

Extension zone 1, stopping distance and stopping time





Continues on next page

## 12 IRB 6620

### 12.1 IRB 6620 2.20 m 150 kg

Continued

#### Extension zone 2, stopping distance and stopping time





Continues on next page



## Category 1, Axis 3

Extension zone 0, stopping distance and stopping time





Continues on next page

## 12 IRB 6620

12.1 IRB 6620 2.20 m 150 kg



Continued

Extension zone 1, stopping distance and stopping time



Continues on next page

## Extension zone 2, stopping distance and stopping time



**This page is intentionally left blank**

## 13 IRB 6650

### 13.1 IRB 6650S 3.00 m 200 kg

#### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	51.5	0.95
2	34.5	0.63
3	20.0	0.32


#### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	1.013
1	1.013	2.026
2	2.026	max reach

#### Category 1, Axis 1

Extension zone 0, stopping distance and stopping time




*Continues on next page*



# 13 IRB 6650

## 13.1 IRB 6650S 3.00 m 200 kg

Continued





### Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



Continues on next page



# 13 IRB 6650

13.1 IRB 6650S 3.00 m 200 kg

Continued

## Category 1, Axis 2



Extension zone 0, stopping distance and stopping time



Continues on next page



Extension zone 1, stopping distance and stopping time





Continues on next page

# 13 IRB 6650

## 13.1 IRB 6650S 3.00 m 200 kg

Continued



### Extension zone 2, stopping distance and stopping time



Continues on next page

## Category 1, Axis 3

Extension zone 0, stopping distance and stopping time





Continues on next page

# 13 IRB 6650

## 13.1 IRB 6650S 3.00 m 200 kg



Continued

### Extension zone 1, stopping distance and stopping time



Continues on next page

## Extension zone 2, stopping distance and stopping time



## 13 IRB 6650

### 13.2 IRB 6650S 3.45 m 125 kg

### 13.2 IRB 6650S 3.45 m 125 kg

#### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	52.8	0.95
2	33.4	0.61
3	20.3	0.32


#### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).


Zone	wcp min (m)	wcp max (m)
0	0	1.161
1	1.161	2.323
2	2.323	max reach

#### Category 1, Axis 1



Extension zone 0, stopping distance and stopping time



Continues on next page



Extension zone 1, stopping distance and stopping time





Continues on next page

# 13 IRB 6650

13.2 IRB 6650S 3.45 m 125 kg

Continued

Extension zone 2, stopping distance and stopping time





Continues on next page



Category 1, Axis 2

Extension zone 0, stopping distance and stopping time





Continues on next page

# 13 IRB 6650

13.2 IRB 6650S 3.45 m 125 kg



Continued

## Extension zone 1, stopping distance and stopping time



Continues on next page

## Extension zone 2, stopping distance and stopping time



Continues on next page



# 13 IRB 6650

13.2 IRB 6650S 3.45 m 125 kg

Continued



## Category 1, Axis 3

Extension zone 0, stopping distance and stopping time



Continues on next page

Extension zone 1, stopping distance and stopping time





Continues on next page

# 13 IRB 6650

## 13.2 IRB 6650S 3.45 m 125 kg

Continued

### Extension zone 2, stopping distance and stopping time



### 13.3 IRB 6650S 3.90 m 90 kg

#### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	51.2	0.97
2	37.0	0.68
3	23.9	0.39


#### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	1.311
1	1.311	2.621
2	2.621	max reach

#### Category 1, Axis 1

Extension zone 0, stopping distance and stopping time




*Continues on next page*



# 13 IRB 6650

## 13.3 IRB 6650S 3.90 m 90 kg

Continued





### Extension zone 1, stopping distance and stopping time



Continues on next page



## Extension zone 2, stopping distance and stopping time



Continues on next page



# 13 IRB 6650

13.3 IRB 6650S 3.90 m 90 kg

Continued



## Category 1, Axis 2

Extension zone 0, stopping distance and stopping time



Continues on next page

## Extension zone 1, stopping distance and stopping time





Continues on next page

# 13 IRB 6650

## 13.3 IRB 6650S 3.90 m 90 kg

Continued



### Extension zone 2, stopping distance and stopping time



Continues on next page

## Category 1, Axis 3

Extension zone 0, stopping distance and stopping time





Continues on next page

# 13 IRB 6650

13.3 IRB 6650S 3.90 m 90 kg



Continued

Extension zone 1, stopping distance and stopping time



Continues on next page

## Extension zone 2, stopping distance and stopping time



13.4 IRB 6650SLeanID 3.0 m 190 kg

Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	45.7	0.83
2	26.2	0.46
3	13.8	0.22


Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	1.013
1	1.013	2.027
2	2.027	max reach


Category 1, Axis 1

Extension zone 0, stopping distance and stopping time





Continues on next page





Extension zone 1, stopping distance and stopping time





Continues on next page

## 13 IRB 6650

13.4 IRB 6650SLeanID 3.0 m 190 kg

Continued



Extension zone 2, stopping distance and stopping time



Continues on next page

## Category 1, Axis 2

## Extension zone 0, stopping distance and stopping time





Continues on next page

# 13 IRB 6650

13.4 IRB 6650SLeanID 3.0 m 190 kg



Continued

Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



Continues on next page



# 13 IRB 6650

13.4 IRB 6650SLeanID 3.0 m 190 kg

Continued



## Category 1, Axis 3

Extension zone 0, stopping distance and stopping time



Continues on next page

Extension zone 1, stopping distance and stopping time





Continues on next page

# 13 IRB 6650

13.4 IRB 6650SLeanID 3.0 m 190 kg

Continued

Extension zone 2, stopping distance and stopping time





## 13.5 IRB 6650SLeanID 3.5 m 100 kg

### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	50.6	0.9
2	34.9	0.66
3	20.5	0.34


### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	1.162
1	1.162	2.323
2	2.323	max reach

### Category 1, Axis 1

Extension zone 0, stopping distance and stopping time




*Continues on next page*



# 13 IRB 6650

13.5 IRB 6650SLeanID 3.5 m 100 kg

Continued





## Extension zone 1, stopping distance and stopping time



Continues on next page



Extension zone 2, stopping distance and stopping time



Continues on next page



Category 1, Axis 2

Extension zone 0, stopping distance and stopping time





Continues on next page

Extension zone 1, stopping distance and stopping time



Continues on next page



Extension zone 2, stopping distance and stopping time



Continues on next page



## Category 1, Axis 3

Extension zone 0, stopping distance and stopping time



Continues on next page



Extension zone 1, stopping distance and stopping time



Continues on next page



## Extension zone 2, stopping distance and stopping time



**This page is intentionally left blank**

## 14 IRB 6660

### 14.1 IRB 6660 1.90 m 205 kg

#### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	21.1	0.32
2	15.1	0.15
3	19.6	0.27


#### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	0.644
1	0.644	1.289
2	1.289	max reach

#### Category 1, Axis 1

Extension zone 0, stopping distance and stopping time




*Continues on next page*



# 14 IRB 6660

## 14.1 IRB 6660 1.90 m 205 kg

Continued





### Extension zone 1, stopping distance and stopping time



Continues on next page

## Extension zone 2, stopping distance and stopping time



Continues on next page



# 14 IRB 6660

14.1 IRB 6660 1.90 m 205 kg

Continued



## Category 1, Axis 2

Extension zone 0, stopping distance and stopping time



Continues on next page

Extension zone 1, stopping distance and stopping time





Continues on next page

## 14 IRB 6660

### 14.1 IRB 6660 1.90 m 205 kg

Continued

#### Extension zone 2, stopping distance and stopping time





Continues on next page



Category 1, Axis 3

Extension zone 0, stopping distance and stopping time





Continues on next page

# 14 IRB 6660

## 14.1 IRB 6660 1.90 m 205 kg



Continued

### Extension zone 1, stopping distance and stopping time



Continues on next page

## Extension zone 2, stopping distance and stopping time



14.2 IRB 6660 3.10 m 130 kg

Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	39.8	0.61
2	34.0	0.42
3	36.6	0.44


Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).


Zone	wcp min (m)	wcp max (m)
0	0	1.035
1	1.035	2.071
2	2.071	max reach

Category 1, Axis 1



Extension zone 0, stopping distance and stopping time



Continues on next page





Extension zone 1, stopping distance and stopping time



Continues on next page



Extension zone 2, stopping distance and stopping time



Continues on next page

Category 1, Axis 2

Extension zone 0, stopping distance and stopping time





Continues on next page

## 14 IRB 6660

### 14.2 IRB 6660 3.10 m 130 kg

Continued



#### Extension zone 1, stopping distance and stopping time



Continues on next page



## Extension zone 2, stopping distance and stopping time



Continues on next page



# 14 IRB 6660

14.2 IRB 6660 3.10 m 130 kg

Continued



## Category 1, Axis 3

Extension zone 0, stopping distance and stopping time





Continues on next page

## Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



## 14.3 IRB 6660 3.35 m 100 kg

### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	40.1	0.63
2	33.9	0.42
3	36.5	0.46


### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	1.118
1	1.118	2.235
2	2.235	max reach

### Category 1, Axis 1

Extension zone 0, stopping distance and stopping time




*Continues on next page*



# 14 IRB 6660

## 14.3 IRB 6660 3.35 m 100 kg

Continued





### Extension zone 1, stopping distance and stopping time



Continues on next page

## Extension zone 2, stopping distance and stopping time



Continues on next page



## 14 IRB 6660

14.3 IRB 6660 3.35 m 100 kg

Continued

### Category 1, Axis 2



Extension zone 0, stopping distance and stopping time



Continues on next page





## Extension zone 1, stopping distance and stopping time



Continues on next page

Continued



Extension zone 2, stopping distance and stopping time



Continues on next page

Category 1, Axis 3



Extension zone 0, stopping distance and stopping time



Continues on next page



Continued

Extension zone 1, stopping distance and stopping time



Continues on next page

## Extension zone 2, stopping distance and stopping time



**This page is intentionally left blank**

## 15 IRB 6700

### 15.1 IRB 6700 2.60 m 200 kg

#### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	40.8	0.66
2	25.1	0.37
3	19.3	0.25


#### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	0.867
1	0.867	1.734
2	1.734	max reach

#### Category 1, Axis 1

Extension zone 0, stopping distance and stopping time




*Continues on next page*



# 15 IRB 6700

## 15.1 IRB 6700 2.60 m 200 kg

Continued





### Extension zone 1, stopping distance and stopping time



Continues on next page



## Extension zone 2, stopping distance and stopping time



Continues on next page



# 15 IRB 6700

15.1 IRB 6700 2.60 m 200 kg

Continued



## Category 1, Axis 2

Extension zone 0, stopping distance and stopping time



Continues on next page

Extension zone 1, stopping distance and stopping time





Continues on next page

# 15 IRB 6700

## 15.1 IRB 6700 2.60 m 200 kg

Continued



### Extension zone 2, stopping distance and stopping time



Continues on next page

Category 1, Axis 3

Extension zone 0, stopping distance and stopping time





Continues on next page

# 15 IRB 6700

15.1 IRB 6700 2.60 m 200 kg



Continued

## Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



## 15 IRB 6700

15.2 IRB 6700 2.65 m 235 kg

### 15.2 IRB 6700 2.65 m 235 kg

#### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	38.2	0.68
2	20.3	0.37
3	14.4	0.22


#### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	0.883
1	0.883	1.767
2	1.767	max reach


#### Category 1, Axis 1

Extension zone 0, stopping distance and stopping time





Continues on next page





Extension zone 1, stopping distance and stopping time





Continues on next page

## 15 IRB 6700

15.2 IRB 6700 2.65 m 235 kg

Continued



Extension zone 2, stopping distance and stopping time



Continues on next page

Category 1, Axis 2

Extension zone 0, stopping distance and stopping time





Continues on next page

# 15 IRB 6700

15.2 IRB 6700 2.65 m 235 kg



Continued

## Extension zone 1, stopping distance and stopping time



Continues on next page

## Extension zone 2, stopping distance and stopping time



Continues on next page



# 15 IRB 6700

15.2 IRB 6700 2.65 m 235 kg

Continued



## Category 1, Axis 3

Extension zone 0, stopping distance and stopping time



Continues on next page

Extension zone 1, stopping distance and stopping time





Continues on next page

# 15 IRB 6700

15.2 IRB 6700 2.65 m 235 kg

Continued

Extension zone 2, stopping distance and stopping time





## 15.3 IRB 6700 2.70 m 300 kg

### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	37.4	0.66
2	21.6	0.39
3	17.5	0.27


### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	0.907
1	0.907	1.813
2	1.813	max reach

### Category 1, Axis 1

Extension zone 0, stopping distance and stopping time




*Continues on next page*



# 15 IRB 6700

15.3 IRB 6700 2.70 m 300 kg

Continued





Extension zone 1, stopping distance and stopping time



Continues on next page

## Extension zone 2, stopping distance and stopping time



Continues on next page



# 15 IRB 6700

15.3 IRB 6700 2.70 m 300 kg

Continued



## Category 1, Axis 2

Extension zone 0, stopping distance and stopping time





Continues on next page

## Extension zone 1, stopping distance and stopping time



Continues on next page



Extension zone 2, stopping distance and stopping time



Continues on next page

## Category 1, Axis 3

Extension zone 0, stopping distance and stopping time





Continues on next page

# 15 IRB 6700

15.3 IRB 6700 2.70 m 300 kg

Continued



Extension zone 1, stopping distance and stopping time



Continues on next page



## Extension zone 2, stopping distance and stopping time



## 15 IRB 6700

### 15.4 IRB 6700 2.80 m 205 kg

### 15.4 IRB 6700 2.80 m 205 kg

#### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	40.0	0.71
2	20.6	0.37
3	14.1	0.22


#### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).


Zone	wcp min (m)	wcp max (m)
0	0	0.931
1	0.931	1.863
2	1.863	max reach

#### Category 1, Axis 1



Extension zone 0, stopping distance and stopping time



Continues on next page



Extension zone 1, stopping distance and stopping time





Continues on next page

# 15 IRB 6700

15.4 IRB 6700 2.80 m 205 kg

Continued



Extension zone 2, stopping distance and stopping time



Continues on next page

Category 1, Axis 2

Extension zone 0, stopping distance and stopping time





Continues on next page

# 15 IRB 6700

15.4 IRB 6700 2.80 m 205 kg



Continued

## Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



Continues on next page



# 15 IRB 6700

15.4 IRB 6700 2.80 m 205 kg

Continued

## Category 1, Axis 3



Extension zone 0, stopping distance and stopping time



Continues on next page



Extension zone 1, stopping distance and stopping time





Continues on next page

# 15 IRB 6700

15.4 IRB 6700 2.80 m 205 kg

Continued

Extension zone 2, stopping distance and stopping time



## 15.5 IRB 6700 2.85 m 155 kg

### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	40.9	0.66
2	25.1	0.37
3	19.3	0.25


### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	0.949
1	0.949	1.898
2	1.898	max reach

### Category 1, Axis 1

Extension zone 0, stopping distance and stopping time




*Continues on next page*



# 15 IRB 6700

15.5 IRB 6700 2.85 m 155 kg

Continued





## Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



Continues on next page



# 15 IRB 6700

15.5 IRB 6700 2.85 m 155 kg

Continued



## Category 1, Axis 2

Extension zone 0, stopping distance and stopping time



Continues on next page

Extension zone 1, stopping distance and stopping time





Continues on next page

## 15 IRB 6700

15.5 IRB 6700 2.85 m 155 kg

Continued

Extension zone 2, stopping distance and stopping time





Continues on next page



## Category 1, Axis 3

Extension zone 0, stopping distance and stopping time





Continues on next page

## 15 IRB 6700

15.5 IRB 6700 2.85 m 155 kg



Continued

Extension zone 1, stopping distance and stopping time



Continues on next page

## Extension zone 2, stopping distance and stopping time



## 15 IRB 6700

15.6 IRB 6700 3.00 m 245 kg

### 15.6 IRB 6700 3.00 m 245 kg

#### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	38.8	0.68
2	21.7	0.39
3	17.9	0.29


#### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).


Zone	wcp min (m)	wcp max (m)
0	0	0.989
1	0.989	1.978
2	1.978	max reach

#### Category 1, Axis 1



Extension zone 0, stopping distance and stopping time



Continues on next page





Extension zone 1, stopping distance and stopping time



Continues on next page



Extension zone 2, stopping distance and stopping time



Continues on next page

Category 1, Axis 2

Extension zone 0, stopping distance and stopping time





Continues on next page

# 15 IRB 6700

15.6 IRB 6700 3.00 m 245 kg

Continued



## Extension zone 1, stopping distance and stopping time



Continues on next page



Extension zone 2, stopping distance and stopping time



Continues on next page



# 15 IRB 6700

15.6 IRB 6700 3.00 m 245 kg

Continued



## Category 1, Axis 3

Extension zone 0, stopping distance and stopping time



Continues on next page

Extension zone 1, stopping distance and stopping time





Continues on next page

# 15 IRB 6700

15.6 IRB 6700 3.00 m 245 kg

Continued

## Extension zone 2, stopping distance and stopping time



## 15.7 IRB 6700 3.05 m 175 kg

### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	40.9	0.73
2	21.1	0.37
3	15.6	0.25


### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	1.019
1	1.019	2.037
2	2.037	max reach

### Category 1, Axis 1

Extension zone 0, stopping distance and stopping time




*Continues on next page*



# 15 IRB 6700

15.7 IRB 6700 3.05 m 175 kg

Continued





## Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



Continues on next page



# 15 IRB 6700

15.7 IRB 6700 3.05 m 175 kg

Continued

## Category 1, Axis 2



Extension zone 0, stopping distance and stopping time



Continues on next page





Extension zone 1, stopping distance and stopping time



Continues on next page



Extension zone 2, stopping distance and stopping time



Continues on next page

Category 1, Axis 3

Extension zone 0, stopping distance and stopping time





Continues on next page

## 15 IRB 6700

15.7 IRB 6700 3.05 m 175 kg



Continued

Extension zone 1, stopping distance and stopping time



Continues on next page

## Extension zone 2, stopping distance and stopping time



15.8 IRB 6700 3.20 m 150 kg

Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	41.7	0.75
2	21.3	0.39
3	15.7	0.25


Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).


Zone	wcp min (m)	wcp max (m)
0	0	1.067
1	1.067	2.133
2	2.133	max reach

Category 1, Axis 1



Extension zone 0, stopping distance and stopping time



Continues on next page



Extension zone 1, stopping distance and stopping time





Continues on next page

# 15 IRB 6700

15.8 IRB 6700 3.20 m 150 kg

Continued

## Extension zone 2, stopping distance and stopping time





Continues on next page



Category 1, Axis 2

Extension zone 0, stopping distance and stopping time





Continues on next page

# 15 IRB 6700

15.8 IRB 6700 3.20 m 150 kg



Continued

## Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



Continues on next page



# 15 IRB 6700

15.8 IRB 6700 3.20 m 150 kg

Continued



## Category 1, Axis 3

Extension zone 0, stopping distance and stopping time



Continues on next page

Extension zone 1, stopping distance and stopping time





Continues on next page

# 15 IRB 6700

15.8 IRB 6700 3.20 m 150 kg

Continued

## Extension zone 2, stopping distance and stopping time



## 15.9 IRB 6700Inv LeanID m 2.60 kg

### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	33.1	0.58
2	21.0	0.37
3	14.7	0.22


### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	0.872
1	0.872	1.744
2	1.744	max reach

### Category 1, Axis 1

Extension zone 0, stopping distance and stopping time




*Continues on next page*



# 15 IRB 6700

15.9 IRB 6700Inv LeanID m 2.60 kg

Continued





## Extension zone 1, stopping distance and stopping time



Continues on next page



Extension zone 2, stopping distance and stopping time



Continues on next page



# 15 IRB 6700

15.9 IRB 6700Inv LeanID m 2.60 kg

Continued



## Category 1, Axis 2

Extension zone 0, stopping distance and stopping time





Continues on next page

Extension zone 1, stopping distance and stopping time



Continues on next page



Extension zone 2, stopping distance and stopping time



Continues on next page

## Category 1, Axis 3



Extension zone 0, stopping distance and stopping time



Continues on next page



Continued

Extension zone 1, stopping distance and stopping time



Continues on next page

## Extension zone 2, stopping distance and stopping time



15.10 IRB 6700Inv LeanID m 2.90 kg

Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	33.1	0.56
2	21.1	0.37
3	14.6	0.22


Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	0.955
1	0.955	1.909
2	1.909	max reach


Category 1, Axis 1

Extension zone 0, stopping distance and stopping time





Continues on next page







Extension zone 1, stopping distance and stopping time



Continues on next page



Extension zone 2, stopping distance and stopping time



Continues on next page

Category 1, Axis 2

Extension zone 0, stopping distance and stopping time





Continues on next page

# 15 IRB 6700

15.10 IRB 6700Inv LeanID m 2.90 kg



Continued

## Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



Continues on next page



# 15 IRB 6700

15.10 IRB 6700Inv LeanID m 2.90 kg

Continued



## Category 1, Axis 3

Extension zone 0, stopping distance and stopping time





Continues on next page

Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time





## 15.11 IRB 6700Inv 2.60 m 300 kg

### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	32.5	0.56
2	20.3	0.34
3	13.8	0.2


### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	0.872
1	0.872	1.744
2	1.744	max reach

### Category 1, Axis 1

Extension zone 0, stopping distance and stopping time




Continues on next page



# 15 IRB 6700

15.11 IRB 6700Inv 2.60 m 300 kg

Continued





## Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



Continues on next page



# 15 IRB 6700

15.11 IRB 6700Inv 2.60 m 300 kg

Continued



## Category 1, Axis 2

Extension zone 0, stopping distance and stopping time





Continues on next page

Extension zone 1, stopping distance and stopping time



Continues on next page



Extension zone 2, stopping distance and stopping time



Continues on next page

## Category 1, Axis 3

Extension zone 0, stopping distance and stopping time





Continues on next page

# 15 IRB 6700

15.11 IRB 6700Inv 2.60 m 300 kg

Continued



Extension zone 1, stopping distance and stopping time



Continues on next page



## Extension zone 2, stopping distance and stopping time



15.12 IRB 6700Inv 2.90 m 245 kg

Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	31.4	0.54
2	20.0	0.34
3	13.2	0.2


Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).


Zone	wcp min (m)	wcp max (m)
0	0	0.955
1	0.955	1.909
2	1.909	max reach

Category 1, Axis 1



Extension zone 0, stopping distance and stopping time



Continues on next page





Extension zone 1, stopping distance and stopping time



Continues on next page



Extension zone 2, stopping distance and stopping time



Continues on next page



## Category 1, Axis 2

## Extension zone 0, stopping distance and stopping time





Continues on next page

Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



Continues on next page



## 15 IRB 6700

15.12 IRB 6700Inv 2.90 m 245 kg

Continued

### Category 1, Axis 3



Extension zone 0, stopping distance and stopping time



Continues on next page





## Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



## 15.13 IRB 6700LeanID 2.60 m 175 kg

### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	36.6	0.58
2	24.4	0.34
3	15.7	0.2


### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	0.867
1	0.867	1.734
2	1.734	max reach

### Category 1, Axis 1

Extension zone 0, stopping distance and stopping time




*Continues on next page*



# 15 IRB 6700

15.13 IRB 6700LeanID 2.60 m 175 kg

Continued





## Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



Continues on next page



## 15 IRB 6700

15.13 IRB 6700LeanID 2.60 m 175 kg

Continued



### Category 1, Axis 2

Extension zone 0, stopping distance and stopping time



Continues on next page



Extension zone 1, stopping distance and stopping time



Continues on next page

Continued

Extension zone 2, stopping distance and stopping time





Continues on next page



Category 1, Axis 3



Extension zone 0, stopping distance and stopping time



Continues on next page



Continued

Extension zone 1, stopping distance and stopping time



Continues on next page

## Extension zone 2, stopping distance and stopping time



15.14 IRB 6700LeanID 2.65 m 220 kg

Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	35.8	0.63
2	19.5	0.34
3	12.3	0.17


Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).


Zone	wcp min (m)	wcp max (m)
0	0	0.883
1	0.883	1.767
2	1.767	max reach

Category 1, Axis 1



Extension zone 0, stopping distance and stopping time



Continues on next page





Extension zone 1, stopping distance and stopping time



Continues on next page



Extension zone 2, stopping distance and stopping time



Continues on next page

Category 1, Axis 2



Extension zone 0, stopping distance and stopping time



Continues on next page

Continued



Extension zone 1, stopping distance and stopping time



Continues on next page



Extension zone 2, stopping distance and stopping time



Continues on next page



## 15 IRB 6700

15.14 IRB 6700LeanID 2.65 m 220 kg

Continued



### Category 1, Axis 3

Extension zone 0, stopping distance and stopping time



Continues on next page

Extension zone 1, stopping distance and stopping time





Continues on next page

# 15 IRB 6700

15.14 IRB 6700LeanID 2.65 m 220 kg

Continued

## Extension zone 2, stopping distance and stopping time



## 15.15 IRB 6700LeanID 2.70 m 270 kg

### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	35.2	0.61
2	20.8	0.37
3	14.9	0.22


### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	0.907
1	0.907	1.813
2	1.813	max reach

### Category 1, Axis 1

Extension zone 0, stopping distance and stopping time




Continues on next page



# 15 IRB 6700

15.15 IRB 6700LeanID 2.70 m 270 kg

Continued





## Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



Continues on next page



## 15 IRB 6700

15.15 IRB 6700LeanID 2.70 m 270 kg

Continued

### Category 1, Axis 2



Extension zone 0, stopping distance and stopping time



Continues on next page





Extension zone 1, stopping distance and stopping time



Continues on next page



Extension zone 2, stopping distance and stopping time



Continues on next page

## Category 1, Axis 3

Extension zone 0, stopping distance and stopping time





Continues on next page

# 15 IRB 6700

15.15 IRB 6700LeanID 2.70 m 270 kg



Continued

## Extension zone 1, stopping distance and stopping time



Continues on next page

## Extension zone 2, stopping distance and stopping time



15.16 IRB 6700LeanID 2.80 m 200 kg

Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	39.0	0.68
2	20.3	0.37
3	13.2	0.2


Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).


Zone	wcp min (m)	wcp max (m)
0	0	0.931
1	0.931	1.863
2	1.863	max reach

Category 1, Axis 1



Extension zone 0, stopping distance and stopping time



Continues on next page





Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time





Continues on next page



## Category 1, Axis 2

## Extension zone 0, stopping distance and stopping time





Continues on next page

# 15 IRB 6700

15.16 IRB 6700LeanID 2.80 m 200 kg



Continued

## Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



Continues on next page



# 15 IRB 6700

15.16 IRB 6700LeanID 2.80 m 200 kg

Continued



## Category 1, Axis 3

Extension zone 0, stopping distance and stopping time



Continues on next page

Extension zone 1, stopping distance and stopping time





Continues on next page

# 15 IRB 6700

15.16 IRB 6700LeanID 2.80 m 200 kg

Continued

## Extension zone 2, stopping distance and stopping time



## 15.17 IRB 6700LeanID 2.85 m 140 kg

### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	38.9	0.61
2	25.0	0.37
3	17.7	0.22


### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	0.949
1	0.949	1.898
2	1.898	max reach

### Category 1, Axis 1

Extension zone 0, stopping distance and stopping time




*Continues on next page*



# 15 IRB 6700

15.17 IRB 6700LeanID 2.85 m 140 kg

Continued





## Extension zone 1, stopping distance and stopping time



Continues on next page



Extension zone 2, stopping distance and stopping time



Continues on next page



# 15 IRB 6700

15.17 IRB 6700LeanID 2.85 m 140 kg

Continued



## Category 1, Axis 2

Extension zone 0, stopping distance and stopping time



Continues on next page

Extension zone 1, stopping distance and stopping time





Continues on next page

# 15 IRB 6700

15.17 IRB 6700LeanID 2.85 m 140 kg

Continued



Extension zone 2, stopping distance and stopping time



Continues on next page

## Category 1, Axis 3



Extension zone 0, stopping distance and stopping time



Continues on next page



Continued

Extension zone 1, stopping distance and stopping time



Continues on next page

## Extension zone 2, stopping distance and stopping time



15.18 IRB 6700LeanID 3.00 m 220 kg

Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	36.6	0.63
2	20.9	0.37
3	16.1	0.25


Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	0.989
1	0.989	1.978
2	1.978	max reach


Category 1, Axis 1

Extension zone 0, stopping distance and stopping time





Continues on next page







Extension zone 1, stopping distance and stopping time



Continues on next page



Extension zone 2, stopping distance and stopping time



Continues on next page

Category 1, Axis 2

Extension zone 0, stopping distance and stopping time





Continues on next page

# 15 IRB 6700

15.18 IRB 6700LeanID 3.00 m 220 kg



Continued

## Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



Continues on next page



## 15 IRB 6700

15.18 IRB 6700LeanID 3.00 m 220 kg

Continued



### Category 1, Axis 3

Extension zone 0, stopping distance and stopping time



Continues on next page

Extension zone 1, stopping distance and stopping time





Continues on next page

# 15 IRB 6700

15.18 IRB 6700LeanID 3.00 m 220 kg

Continued

## Extension zone 2, stopping distance and stopping time





## 15.19 IRB 6700LeanID 3.05 m 155 kg

### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	38.4	0.68
2	20.2	0.37
3	14.2	0.22


### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	1.019
1	1.019	2.037
2	2.037	max reach

### Category 1, Axis 1

Extension zone 0, stopping distance and stopping time




*Continues on next page*



# 15 IRB 6700

15.19 IRB 6700LeanID 3.05 m 155 kg

Continued





## Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



Continues on next page



# 15 IRB 6700

15.19 IRB 6700LeanID 3.05 m 155 kg

Continued



## Category 1, Axis 2

Extension zone 0, stopping distance and stopping time





Continues on next page

Extension zone 1, stopping distance and stopping time



Continues on next page



Extension zone 2, stopping distance and stopping time



Continues on next page

Category 1, Axis 3

Extension zone 0, stopping distance and stopping time





Continues on next page

## 15 IRB 6700

15.19 IRB 6700LeanID 3.05 m 155 kg

Continued



Extension zone 1, stopping distance and stopping time



Continues on next page



## Extension zone 2, stopping distance and stopping time



15.20 IRB 6700LeanID 3.20 m 145 kg

Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	40.6	0.73
2	20.9	0.37
3	14.7	0.22


Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).


Zone	wcp min (m)	wcp max (m)
0	0	1.067
1	1.067	2.133
2	2.133	max reach

Category 1, Axis 1



Extension zone 0, stopping distance and stopping time



Continues on next page





Extension zone 1, stopping distance and stopping time



Continues on next page



Extension zone 2, stopping distance and stopping time



Continues on next page

Category 1, Axis 2

Extension zone 0, stopping distance and stopping time





Continues on next page

# 15 IRB 6700

15.20 IRB 6700LeanID 3.20 m 145 kg



Continued

## Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



Continues on next page



# 15 IRB 6700

15.20 IRB 6700LeanID 3.20 m 145 kg

Continued

## Category 1, Axis 3



Extension zone 0, stopping distance and stopping time



Continues on next page



## Extension zone 1, stopping distance and stopping time





Continues on next page

# 15 IRB 6700

15.20 IRB 6700LeanID 3.20 m 145 kg

Continued

## Extension zone 2, stopping distance and stopping time



## 16 IRB 6790

### 16.1 IRB 6790 2.65 m 235 kg

#### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	38.2	0.68
2	20.3	0.37
3	14.4	0.22


#### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	0.883
1	0.883	1.767
2	1.767	max reach

#### Category 1, Axis 1

Extension zone 0, stopping distance and stopping time




*Continues on next page*



# 16 IRB 6790

16.1 IRB 6790 2.65 m 235 kg

Continued





## Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



Continues on next page



# 16 IRB 6790

16.1 IRB 6790 2.65 m 235 kg

Continued



## Category 1, Axis 2

Extension zone 0, stopping distance and stopping time



Continues on next page

## Extension zone 1, stopping distance and stopping time





Continues on next page

## 16 IRB 6790

16.1 IRB 6790 2.65 m 235 kg

Continued

Extension zone 2, stopping distance and stopping time





Continues on next page



## Category 1, Axis 3



Extension zone 0, stopping distance and stopping time



Continues on next page



Continued

Extension zone 1, stopping distance and stopping time



Continues on next page

## Extension zone 2, stopping distance and stopping time



## 16 IRB 6790

16.2 IRB 6790 2.80 m 205 kg

### 16.2 IRB 6790 2.80 m 205 kg

#### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	40.0	0.71
2	20.6	0.37
3	14.1	0.22


#### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).


Zone	wcp min (m)	wcp max (m)
0	0	0.931
1	0.931	1.863
2	1.863	max reach

#### Category 1, Axis 1



Extension zone 0, stopping distance and stopping time



Continues on next page





Extension zone 1, stopping distance and stopping time



Continues on next page



Extension zone 2, stopping distance and stopping time



Continues on next page

Category 1, Axis 2

Extension zone 0, stopping distance and stopping time





Continues on next page

# 16 IRB 6790

16.2 IRB 6790 2.80 m 205 kg

Continued



## Extension zone 1, stopping distance and stopping time



Continues on next page



Extension zone 2, stopping distance and stopping time



Continues on next page



# 16 IRB 6790

16.2 IRB 6790 2.80 m 205 kg

Continued



## Category 1, Axis 3

Extension zone 0, stopping distance and stopping time





Continues on next page

Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



## 17 IRB 7600

### 17.1 IRB 7600 2.55 m 400 kg

#### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	31.6	0.73
2	13.1	0.37
3	9.0	0.22


#### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	0.85
1	0.85	1.7
2	1.7	max reach

#### Category 1, Axis 1

Extension zone 0, stopping distance and stopping time




*Continues on next page*



# 17 IRB 7600

## 17.1 IRB 7600 2.55 m 400 kg

Continued





### Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



Continues on next page



# 17 IRB 7600

17.1 IRB 7600 2.55 m 400 kg

Continued

## Category 1, Axis 2



Extension zone 0, stopping distance and stopping time



Continues on next page



Extension zone 1, stopping distance and stopping time





Continues on next page

# 17 IRB 7600

17.1 IRB 7600 2.55 m 400 kg

Continued



Extension zone 2, stopping distance and stopping time



Continues on next page

Category 1, Axis 3

Extension zone 0, stopping distance and stopping time





Continues on next page

## 17 IRB 7600

17.1 IRB 7600 2.55 m 400 kg



Continued

Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



## 17 IRB 7600

17.2 IRB 7600 2.55 m 500 kg

### 17.2 IRB 7600 2.55 m 500 kg

#### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	32.6	0.75
2	9.0	0.29
3	7.6	0.2


#### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).


Zone	wcp min (m)	wcp max (m)
0	0	0.85
1	0.85	1.7
2	1.7	max reach

#### Category 1, Axis 1



Extension zone 0, stopping distance and stopping time



Continues on next page



Extension zone 1, stopping distance and stopping time





Continues on next page

## 17 IRB 7600

17.2 IRB 7600 2.55 m 500 kg

Continued

Extension zone 2, stopping distance and stopping time





Continues on next page



Category 1, Axis 2

Extension zone 0, stopping distance and stopping time





Continues on next page

## 17 IRB 7600

17.2 IRB 7600 2.55 m 500 kg



Continued

Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



Continues on next page



# 17 IRB 7600

17.2 IRB 7600 2.55 m 500 kg

Continued



## Category 1, Axis 3

Extension zone 0, stopping distance and stopping time



Continues on next page

Extension zone 1, stopping distance and stopping time





Continues on next page

## 17 IRB 7600

17.2 IRB 7600 2.55 m 500 kg

Continued

Extension zone 2, stopping distance and stopping time



## 17.3 IRB 7600 2.80 m 340 kg

### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	31.1	0.71
2	12.9	0.37
3	9.0	0.22


### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	0.932
1	0.932	1.865
2	1.865	max reach

### Category 1, Axis 1

Extension zone 0, stopping distance and stopping time




Continues on next page



# 17 IRB 7600

17.3 IRB 7600 2.80 m 340 kg

Continued





## Extension zone 1, stopping distance and stopping time



Continues on next page



## Extension zone 2, stopping distance and stopping time



Continues on next page



# 17 IRB 7600

17.3 IRB 7600 2.80 m 340 kg

Continued



## Category 1, Axis 2

Extension zone 0, stopping distance and stopping time



Continues on next page

Extension zone 1, stopping distance and stopping time





Continues on next page

## 17 IRB 7600

17.3 IRB 7600 2.80 m 340 kg

Continued



Extension zone 2, stopping distance and stopping time



Continues on next page

Category 1, Axis 3

Extension zone 0, stopping distance and stopping time





Continues on next page

## 17 IRB 7600

17.3 IRB 7600 2.80 m 340 kg



Continued

Extension zone 1, stopping distance and stopping time



Continues on next page

## Extension zone 2, stopping distance and stopping time



## 17 IRB 7600

17.4 IRB 7600 3.05 m 325 kg

### 17.4 IRB 7600 3.05 m 325 kg

#### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	33.0	0.78
2	9.0	0.29
3	8.4	0.22


#### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	1.015
1	1.015	2.03
2	2.03	max reach


#### Category 1, Axis 1

Extension zone 0, stopping distance and stopping time





Continues on next page





Extension zone 1, stopping distance and stopping time





Continues on next page

## 17 IRB 7600

17.4 IRB 7600 3.05 m 325 kg

Continued



Extension zone 2, stopping distance and stopping time



Continues on next page

Category 1, Axis 2

Extension zone 0, stopping distance and stopping time





Continues on next page

# 17 IRB 7600

17.4 IRB 7600 3.05 m 325 kg



Continued

Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



Continues on next page



## 17 IRB 7600

17.4 IRB 7600 3.05 m 325 kg

Continued



### Category 1, Axis 3

Extension zone 0, stopping distance and stopping time



Continues on next page

Extension zone 1, stopping distance and stopping time





Continues on next page

# 17 IRB 7600

17.4 IRB 7600 3.05 m 325 kg

Continued

## Extension zone 2, stopping distance and stopping time





## 17.5 IRB 7600 3.50 m 150 kg

### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	47.1	0.85
2	11.5	0.32
3	8.8	0.22


### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	1.167
1	1.167	2.333
2	2.333	max reach

### Category 1, Axis 1

Extension zone 0, stopping distance and stopping time




*Continues on next page*



# 17 IRB 7600

17.5 IRB 7600 3.50 m 150 kg

Continued





## Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



Continues on next page



# 17 IRB 7600

17.5 IRB 7600 3.50 m 150 kg

Continued



## Category 1, Axis 2

Extension zone 0, stopping distance and stopping time



Continues on next page

Extension zone 1, stopping distance and stopping time





Continues on next page

## 17 IRB 7600

17.5 IRB 7600 3.50 m 150 kg

Continued



Extension zone 2, stopping distance and stopping time



Continues on next page

Category 1, Axis 3

Extension zone 0, stopping distance and stopping time





Continues on next page

## 17 IRB 7600

17.5 IRB 7600 3.50 m 150 kg

Continued



Extension zone 1, stopping distance and stopping time



Continues on next page



## Extension zone 2, stopping distance and stopping time



## 17 IRB 7600

17.6 IRB 7600LeanID 2.55 m 390 kg

### 17.6 IRB 7600LeanID 2.55 m 390 kg

#### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	27.5	0.63
2	10.3	0.29
3	6.8	0.17


#### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).


Zone	wcp min (m)	wcp max (m)
0	0	0.85
1	0.85	1.7
2	1.7	max reach

#### Category 1, Axis 1



Extension zone 0, stopping distance and stopping time



Continues on next page



Extension zone 1, stopping distance and stopping time





Continues on next page

# 17 IRB 7600

17.6 IRB 7600LeanID 2.55 m 390 kg

Continued



## Extension zone 2, stopping distance and stopping time



Continues on next page

Category 1, Axis 2

Extension zone 0, stopping distance and stopping time





Continues on next page

# 17 IRB 7600

17.6 IRB 7600LeanID 2.55 m 390 kg



Continued

## Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



Continues on next page



## 17 IRB 7600

17.6 IRB 7600LeanID 2.55 m 390 kg

Continued

### Category 1, Axis 3



Extension zone 0, stopping distance and stopping time



Continues on next page



Extension zone 1, stopping distance and stopping time





Continues on next page

## 17 IRB 7600

17.6 IRB 7600LeanID 2.55 m 390 kg

Continued

Extension zone 2, stopping distance and stopping time



## 17.7 IRB 7600LeanID 2.8 m 320 kg

### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	28.3	0.66
2	10.7	0.32
3	7.2	0.17


### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	0.932
1	0.932	1.865
2	1.865	max reach

### Category 1, Axis 1

Extension zone 0, stopping distance and stopping time




Continues on next page



# 17 IRB 7600

17.7 IRB 7600LeanID 2.8 m 320 kg

Continued





## Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



Continues on next page



# 17 IRB 7600

17.7 IRB 7600LeanID 2.8 m 320 kg

Continued



## Category 1, Axis 2

Extension zone 0, stopping distance and stopping time



Continues on next page

Extension zone 1, stopping distance and stopping time





Continues on next page

# 17 IRB 7600

17.7 IRB 7600LeanID 2.8 m 320 kg

Continued

## Extension zone 2, stopping distance and stopping time





Continues on next page



Category 1, Axis 3

Extension zone 0, stopping distance and stopping time





Continues on next page

## 17 IRB 7600

17.7 IRB 7600LeanID 2.8 m 320 kg



Continued

Extension zone 1, stopping distance and stopping time



Continues on next page

## Extension zone 2, stopping distance and stopping time



## 17 IRB 7600

17.8 IRB 7600LeanID 3.1 m 290 kg

### 17.8 IRB 7600LeanID 3.1 m 290 kg

#### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	30.1	0.71
2	8.4	0.27
3	6.7	0.17


#### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).


Zone	wcp min (m)	wcp max (m)
0	0	1.015
1	1.015	2.03
2	2.03	max reach

#### Category 1, Axis 1



Extension zone 0, stopping distance and stopping time



Continues on next page





Extension zone 1, stopping distance and stopping time



Continues on next page

Continued



Extension zone 2, stopping distance and stopping time



Continues on next page

Category 1, Axis 2

Extension zone 0, stopping distance and stopping time





Continues on next page

# 17 IRB 7600

17.8 IRB 7600LeanID 3.1 m 290 kg

Continued



## Extension zone 1, stopping distance and stopping time



Continues on next page



Extension zone 2, stopping distance and stopping time



Continues on next page



# 17 IRB 7600

17.8 IRB 7600LeanID 3.1 m 290 kg

Continued



## Category 1, Axis 3

Extension zone 0, stopping distance and stopping time



Continues on next page

Extension zone 1, stopping distance and stopping time





Continues on next page

# 17 IRB 7600

17.8 IRB 7600LeanID 3.1 m 290 kg

Continued

## Extension zone 2, stopping distance and stopping time



## 18 IRB 8700

### 18.1 IRB 8700 3.50 m 800 kg

#### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	44.4	1.31
2	11.4	0.32
3	13.0	0.37


#### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	1.169
1	1.169	2.338
2	2.338	max reach

#### Category 1, Axis 1

Extension zone 0, stopping distance and stopping time




*Continues on next page*



# 18 IRB 8700

## 18.1 IRB 8700 3.50 m 800 kg

Continued





### Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



Continues on next page



# 18 IRB 8700

18.1 IRB 8700 3.50 m 800 kg

Continued

## Category 1, Axis 2



Extension zone 0, stopping distance and stopping time



Continues on next page



Extension zone 1, stopping distance and stopping time





Continues on next page

# 18 IRB 8700

## 18.1 IRB 8700 3.50 m 800 kg

Continued



### Extension zone 2, stopping distance and stopping time



Continues on next page

Category 1, Axis 3

Extension zone 0, stopping distance and stopping time





Continues on next page

# 18 IRB 8700

18.1 IRB 8700 3.50 m 800 kg



Continued

Extension zone 1, stopping distance and stopping time



Continues on next page

## Extension zone 2, stopping distance and stopping time



## 18 IRB 8700

18.2 IRB 8700 4.20 m 550 kg

### 18.2 IRB 8700 4.20 m 550 kg

#### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	44.4	1.33
2	10.0	0.27
3	14.4	0.44


#### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).


Zone	wcp min (m)	wcp max (m)
0	0	1.399
1	1.399	2.798
2	2.798	max reach

#### Category 1, Axis 1



Extension zone 0, stopping distance and stopping time



Continues on next page



Extension zone 1, stopping distance and stopping time





Continues on next page

# 18 IRB 8700

18.2 IRB 8700 4.20 m 550 kg

Continued

Extension zone 2, stopping distance and stopping time





Continues on next page



Category 1, Axis 2

Extension zone 0, stopping distance and stopping time





Continues on next page

# 18 IRB 8700

18.2 IRB 8700 4.20 m 550 kg



Continued

## Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



Continues on next page



# 18 IRB 8700

18.2 IRB 8700 4.20 m 550 kg

Continued



## Category 1, Axis 3

Extension zone 0, stopping distance and stopping time



Continues on next page

## Extension zone 1, stopping distance and stopping time





Continues on next page

# 18 IRB 8700

18.2 IRB 8700 4.20 m 550 kg

Continued

## Extension zone 2, stopping distance and stopping time



## 18.3 IRB 8700LeanID 3.50 m 630 kg

### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	44.4	1.19
2	10.1	0.27
3	9.6	0.25


### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	1.169
1	1.169	2.338
2	2.338	max reach


### Category 1, Axis 1

Extension zone 0, stopping distance and stopping time





*Continues on next page*

Continued





Extension zone 1, stopping distance and stopping time



Continues on next page



Extension zone 2, stopping distance and stopping time



Continues on next page



# 18 IRB 8700

18.3 IRB 8700LeanID 3.50 m 630 kg

Continued



## Category 1, Axis 2

Extension zone 0, stopping distance and stopping time



Continues on next page



Extension zone 1, stopping distance and stopping time



Continues on next page

Continued



Extension zone 2, stopping distance and stopping time



Continues on next page

## Category 1, Axis 3

Extension zone 0, stopping distance and stopping time





Continues on next page

# 18 IRB 8700

18.3 IRB 8700LeanID 3.50 m 630 kg



Continued

Extension zone 1, stopping distance and stopping time



Continues on next page

## Extension zone 2, stopping distance and stopping time



18.4 IRB 8700LeanID 4.20 m 475 kg

Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	44.4	1.26
2	9.5	0.25
3	12.0	0.34


Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	1.399
1	1.399	2.798
2	2.798	max reach


Category 1, Axis 1

Extension zone 0, stopping distance and stopping time





Continues on next page





Extension zone 1, stopping distance and stopping time





Continues on next page

# 18 IRB 8700

18.4 IRB 8700LeanID 4.20 m 475 kg

Continued



Extension zone 2, stopping distance and stopping time



Continues on next page

## Category 1, Axis 2

## Extension zone 0, stopping distance and stopping time





Continues on next page

# 18 IRB 8700

18.4 IRB 8700LeanID 4.20 m 475 kg



Continued

Extension zone 1, stopping distance and stopping time



Continues on next page



Extension zone 2, stopping distance and stopping time



Continues on next page



Category 1, Axis 3

Extension zone 0, stopping distance and stopping time





Continues on next page

Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time





# 19 IRB 460

## 19.1 IRB 460 2.4 m 110 kg

### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	41.5	0.49
2	14.6	0.17
3	13.6	0.15


### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	0.889
1	0.889	1.778
2	1.778	max reach

### Category 1, Axis 1

Extension zone 0, stopping distance and stopping time




*Continues on next page*



# 19 IRB 460

## 19.1 IRB 460 2.4 m 110 kg

Continued





### Extension zone 1, stopping distance and stopping time



Continues on next page

## Extension zone 2, stopping distance and stopping time



Continues on next page



# 19 IRB 460

19.1 IRB 460 2.4 m 110 kg

Continued



## Category 1, Axis 2

Extension zone 0, stopping distance and stopping time



Continues on next page

Extension zone 1, stopping distance and stopping time





Continues on next page

## 19 IRB 460

### 19.1 IRB 460 2.4 m 110 kg

Continued



#### Extension zone 2, stopping distance and stopping time



Continues on next page

Category 1, Axis 3

Extension zone 0, stopping distance and stopping time





Continues on next page

## 19 IRB 460

### 19.1 IRB 460 2.4 m 110 kg

Continued



#### Extension zone 1, stopping distance and stopping time



Continues on next page



## Extension zone 2, stopping distance and stopping time



**This page is intentionally left blank**

## 20 IRB 660

### 20.1 IRB 660 3.15 m 180 kg

#### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	64.4	0.9
2	32.6	0.39
3	27.0	0.29


#### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	1.148
1	1.148	2.297
2	2.297	max reach

#### Category 1, Axis 1

Extension zone 0, stopping distance and stopping time




*Continues on next page*



## 20 IRB 660

20.1 IRB 660 3.15 m 180 kg

Continued





Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



Continues on next page



## 20 IRB 660

20.1 IRB 660 3.15 m 180 kg

Continued



### Category 1, Axis 2

Extension zone 0, stopping distance and stopping time



Continues on next page

Extension zone 1, stopping distance and stopping time





Continues on next page

## 20 IRB 660

20.1 IRB 660 3.15 m 180 kg

Continued

Extension zone 2, stopping distance and stopping time





Continues on next page



## Category 1, Axis 3

Extension zone 0, stopping distance and stopping time





Continues on next page

## 20 IRB 660

20.1 IRB 660 3.15 m 180 kg



*Continued*

Extension zone 1, stopping distance and stopping time



*Continues on next page*

## Extension zone 2, stopping distance and stopping time



## 20 IRB 660

### 20.2 IRB 660 3.15 m 250 kg

### 20.2 IRB 660 3.15 m 250 kg

#### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	43.1	0.78
2	23.2	0.37
3	21.6	0.32


#### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).


Zone	wcp min (m)	wcp max (m)
0	0	1.148
1	1.148	2.297
2	2.297	max reach

#### Category 1, Axis 1



Extension zone 0, stopping distance and stopping time



Continues on next page



Extension zone 1, stopping distance and stopping time





Continues on next page

## 20 IRB 660

20.2 IRB 660 3.15 m 250 kg

Continued



Extension zone 2, stopping distance and stopping time



Continues on next page

## Category 1, Axis 2

Extension zone 0, stopping distance and stopping time





Continues on next page

## 20 IRB 660

20.2 IRB 660 3.15 m 250 kg

Continued



Extension zone 1, stopping distance and stopping time



Continues on next page



Extension zone 2, stopping distance and stopping time



Continues on next page



## 20 IRB 660

20.2 IRB 660 3.15 m 250 kg

Continued



### Category 1, Axis 3

Extension zone 0, stopping distance and stopping time



Continues on next page

Extension zone 1, stopping distance and stopping time





Continues on next page

## 20 IRB 660

20.2 IRB 660 3.15 m 250 kg

Continued

Extension zone 2, stopping distance and stopping time



## 21 IRB 760

### 21.1 IRB 760 3.2 m 445 kg

#### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	40.7	0.89
2	24.4	0.54
3	26.9	0.56


#### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).

Zone	wcp min (m)	wcp max (m)
0	0	1.17
1	1.17	2.34
2	2.34	max reach

#### Category 1, Axis A1

Extension zone 0, stopping distance and stopping time




*Continues on next page*



## 21 IRB 760

### 21.1 IRB 760 3.2 m 445 kg

Continued





### Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



Continues on next page



## 21 IRB 760

21.1 IRB 760 3.2 m 445 kg

Continued

### Category 1, Axis A2



Extension zone 0, stopping distance and stopping time



Continues on next page



Extension zone 1, stopping distance and stopping time





Continues on next page

## 21 IRB 760

21.1 IRB 760 3.2 m 445 kg

Continued



Extension zone 2, stopping distance and stopping time



Continues on next page

## Category 1, Axis A3

## Extension zone 0, stopping distance and stopping time





Continues on next page

## 21 IRB 760

21.1 IRB 760 3.2 m 445 kg



Continued

Extension zone 1, stopping distance and stopping time



Continues on next page

## Extension zone 2, stopping distance and stopping time



## 21 IRB 760

### 21.2 IRB 760 3.2 m 450 kg

### 21.2 IRB 760 3.2 m 450 kg

#### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load. All results are from tests on one moving axis.

Axis	Distance (degrees)	Stop time (s)
1	40.2	0.83
2	0.0	0.0
3	26.4	0.49


#### Category 1, extension zones

For definitions of the zones, see [Extension zones for articulated robots on page 14](#).


Zone	wcp min (m)	wcp max (m)
0	0	1.168
1	1.168	2.337
2	2.337	max reach

#### Category 1, Axis 1



Extension zone 0, stopping distance and stopping time



Continues on next page



Extension zone 1, stopping distance and stopping time





Continues on next page

## 21 IRB 760

21.2 IRB 760 3.2 m 450 kg

Continued

Extension zone 2, stopping distance and stopping time





Continues on next page



Category 1, Axis 2

Extension zone 0, stopping distance and stopping time





Continues on next page

## 21 IRB 760

21.2 IRB 760 3.2 m 450 kg



Continued

Extension zone 1, stopping distance and stopping time



Continues on next page

Extension zone 2, stopping distance and stopping time



Continues on next page



## 21 IRB 760

21.2 IRB 760 3.2 m 450 kg

Continued



### Category 1, Axis 3

Extension zone 0, stopping distance and stopping time



Continues on next page

Extension zone 1, stopping distance and stopping time





Continues on next page

## 21 IRB 760

21.2 IRB 760 3.2 m 450 kg

Continued

Extension zone 2, stopping distance and stopping time



## 22 IRB 360

### 22.1 IRB 360 0.8 m 1 kg

#### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load.

Protection type/variant	Distance (meters)	Stop time (s)
Standard	0.57	0.18
Wash down	0.56	0.18
3AXES	0.57	0.17

*Continues on next page*



## 22 IRB 360

### 22.1 IRB 360 0.8 m 1 kg

Continued

#### Category 1, Standard

#### Stopping distance and stopping time





Continues on next page



Category 1, Wash Down

Stopping distance and stopping time



Continues on next page



## 22 IRB 360

### 22.1 IRB 360 0.8 m 1 kg

Continued

#### Category 1, 3AXES

#### Stopping distance and stopping time



---

**22.2 IRB 360 1.13 m 1 kg**

---

**Category 0**

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load.

Protection type/variant	Distance (meters)	Stop time (s)
Standard	0.69	0.19
Wash down	0.69	0.19
3AXES	0.73	0.18
Stainless	0.67	0.19

*Continues on next page*



## 22 IRB 360

### 22.2 IRB 360 1.13 m 1 kg

Continued

#### Category 1, Standard



#### Stopping distance and stopping time



Continues on next page

Category 1, Wash Down

Stopping distance and stopping time



Continues on next page



## 22 IRB 360

### 22.2 IRB 360 1.13 m 1 kg

Continued

#### Category 1, 3AXES



#### Stopping distance and stopping time



Continues on next page

Category 1, Stainless

Stopping distance and stopping time



## 22 IRB 360

---

### 22.3 IRB 360 1.13 m 3 kg

### 22.3 IRB 360 1.13 m 3 kg

---

#### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load.



Protection type/variant	Distance (meters)	Stop time (s)
Standard	0.65	0.21
Wash down	0.65	0.21
3AXES	0.62	0.20
Stainless	0.64	0.22

*Continues on next page*



Category 1, Standard

Stopping distance and stopping time



Continues on next page



## 22 IRB 360

### 22.3 IRB 360 1.13 m 3 kg

Continued

#### Category 1, Wash Down



#### Stopping distance and stopping time



Continues on next page

Category 1, 3AXES

Stopping distance and stopping time



Continues on next page



## 22 IRB 360

### 22.3 IRB 360 1.13 m 3 kg

Continued

#### Category 1, Stainless

#### Stopping distance and stopping time



---

## 22.4 IRB 360 1.13 m 8 kg

---

### Category 0



The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load.

Protection type/variant	Distance (meters)	Stop time (s)
Standard	0.65	0.33

*Continues on next page*

Category 1, Standard

Stopping distance and stopping time



## 22.5 IRB 360 1.6 m 1 kg

### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load.

Protection type/variant	Distance (meters)	Stop time (s)
Standard	0.90	0.22

*Continues on next page*



## 22 IRB 360

22.5 IRB 360 1.6 m 1 kg

Continued

### Category 1, Standard

#### Stopping distance and stopping time





---

## 22.6 IRB 360 1.6 m 6 kg

---

### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load.

Protection type/variant	Distance (meters)	Stop time (s)
Standard	0.93	0.36

*Continues on next page*



## 22 IRB 360

### 22.6 IRB 360 1.6 m 6 kg

Continued

#### Category 1, Standard

#### Stopping distance and stopping time



## 23 IRB 365

### 23.1 IRB 365 0.8 m 1.5 kg

#### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load.

Protection type/variant	Distance (meters)	Stop time (s)
Standard	0.55	0.25

*Continues on next page*



## 23 IRB 365

### 23.1 IRB 365 0.8 m 1.5 kg

Continued

#### Category 1, Standard

#### Stopping distance and stopping time



## 23.2 IRB 365 1.1 m 1.5 kg

### Category 0



The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load.

Protection type/variant	Distance (meters)	Stop time (s)
Standard	0.41	0.29

*Continues on next page*

Category 1, Standard

Stopping distance and stopping time



## 23.3 IRB 365 1.3 m 1.5 kg

### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load.

Protection type/variant	Distance (meters)	Stop time (s)
Standard	0.73	0.26

*Continues on next page*



## 23 IRB 365

23.3 IRB 365 1.3 m 1.5 kg

Continued

### Category 1, Standard

Stopping distance and stopping time





## 24 IRB 390

### 24.1 IRB 390 1.3 m 10 kg

#### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load.

Protection type/variant	Distance (meters)	Stop time (s)
Standard	0.71	0.29

*Continues on next page*



## 24 IRB 390

### 24.1 IRB 390 1.3 m 10 kg

Continued

#### Category 1, Standard

#### Stopping distance and stopping time



---

## 24.2 IRB 390 1.3 m 15 kg

---

### Category 0

The following table describes the stopping distance and time for category 0 emergency stop at max speed, with the arm stretched out to the maximum with maximum load.

Protection type/variant	Distance (meters)	Stop time (s)
Standard	0.72	0.28

*Continues on next page*



## 24 IRB 390

### 24.2 IRB 390 1.3 m 15 kg

Continued

#### Category 1, Standard

#### Stopping distance and stopping time





# 25 IRBP A

## 25.1 A250\_D1000

### Category 0, ARM

#### Stopping distance and stopping time



*Continues on next page*



# 25 IRBP A

## 25.1 A250\_D1000

Continued

### Category 0, PLATE



#### Stopping distance and stopping time



Continues on next page

Category 1, ARM

Stopping distance and stopping time



Continues on next page



# 25 IRBP A

## 25.1 A250\_D1000

Continued

### Category 1, PLATE

#### Stopping distance and stopping time







25.2 A500\_D1000

Category 0, ARM

Stopping distance and stopping time



Continues on next page



# 25 IRBP A

## 25.2 A500\_D1000

Continued

### Category 0, PLATE



#### Stopping distance and stopping time



Continues on next page

Category 1, ARM



Stopping distance and stopping time



Continues on next page

Category 1, PLATE



Stopping distance and stopping time



25.3 A500\_D1450

Category 0, ARM

Stopping distance and stopping time



Continues on next page



# 25 IRBP A

## 25.3 A500\_D1450

Continued

### Category 0, PLATE



#### Stopping distance and stopping time



Continues on next page

Category 1, ARM



Stopping distance and stopping time



Continues on next page

Category 1, PLATE

Stopping distance and stopping time







## 25.4 A750\_D1000

## Category 0, ARM

## Stopping distance and stopping time

*Continues on next page*



# 25 IRBP A

## 25.4 A750\_D1000

Continued

### Category 0, PLATE



#### Stopping distance and stopping time



Continues on next page

Category 1, ARM



Stopping distance and stopping time



Continues on next page

Category 1, PLATE



Stopping distance and stopping time



25.5 A750\_D1450

Category 0, ARM



Stopping distance and stopping time



Continues on next page

Category 0, PLATE



Stopping distance and stopping time



Continues on next page

Category 1, ARM



Stopping distance and stopping time



Continues on next page

Category 1, PLATE

Stopping distance and stopping time







## 26 IRBP B

### 26.1 B250\_D1000

#### Category 0, INTERCH

#### Stopping distance and stopping time



*Continues on next page*



## 26 IRBP B

### 26.1 B250\_D1000

Continued

#### Category 0, ARM



#### Stopping distance and stopping time



Continues on next page

Category 0, PLATE

Stopping distance and stopping time



Continues on next page



## 26 IRBP B

### 26.1 B250\_D1000

Continued

#### Category 1, INTERCH



#### Stopping distance and stopping time



Continues on next page

Category 1, ARM

Stopping distance and stopping time



Continues on next page



## 26 IRBP B

### 26.1 B250\_D1000

Continued

#### Category 1, PLATE



#### Stopping distance and stopping time



## 26.2 B500\_D1450



## Category 0, INTERCH

## Stopping distance and stopping time

*Continues on next page*

Category 0, ARM

Stopping distance and stopping time





Continues on next page



Category 0, PLATE



Stopping distance and stopping time



Continues on next page

Category 1, INTERCH



Stopping distance and stopping time



Continues on next page

Category 1, ARM



Stopping distance and stopping time



Continues on next page

Category 1, PLATE



Stopping distance and stopping time



## 26.3 B750\_D1450



## Category 0, INTERCH

## Stopping distance and stopping time

*Continues on next page*

Category 0, ARM



Stopping distance and stopping time



Continues on next page

Category 0, PLATE



Stopping distance and stopping time



Continues on next page

Category 1, INTERCH

Stopping distance and stopping time





Continues on next page



Category 1, ARM



Stopping distance and stopping time



Continues on next page

Category 1, PLATE

Stopping distance and stopping time





## 27 IRBP C

### 27.1 C500

#### Category 0, INTERCH

#### Stopping distance and stopping time



*Continues on next page*



# 27 IRBP C

## 27.1 C500

Continued

### Category 1, INTERCH



#### Stopping distance and stopping time



## 27.2 C1000

## Category 0, INTERCH



## Stopping distance and stopping time



Continues on next page

Category 1, INTERCH

Stopping distance and stopping time





## 28 IRBP D

### 28.1 D300\_L1250\_D1000

#### Category 0, INTERCH

#### Stopping distance and stopping time



*Continues on next page*



# 28 IRBP D

## 28.1 D300\_L1250\_D1000

Continued

### Category 0, ARM

#### Stopping distance and stopping time





Continues on next page



Category 0, PLATE



Stopping distance and stopping time



Continues on next page

Category 1, INTERCH



Stopping distance and stopping time



Continues on next page

Category 1, ARM



Stopping distance and stopping time



Continues on next page

Category 1, PLATE



Stopping distance and stopping time



## 28.2 D300\_L1600\_D1000

## Category 0, INTERCH



## Stopping distance and stopping time



Continues on next page

Category 0, ARM



Stopping distance and stopping time



Continues on next page

Category 0, PLATE



Stopping distance and stopping time



Continues on next page

Category 1, INTERCH

Stopping distance and stopping time





Continues on next page



Category 1, ARM



Stopping distance and stopping time



Continues on next page

Category 1, PLATE



Stopping distance and stopping time



## 28.3 D600\_L1600\_D1000

## Category 0, INTERCH



## Stopping distance and stopping time



Continues on next page

Category 0, ARM



Stopping distance and stopping time



Continues on next page

Category 0, PLATE



Stopping distance and stopping time



Continues on next page

Category 1, INTERCH



Stopping distance and stopping time



Continues on next page

Category 1, ARM



Stopping distance and stopping time



Continues on next page

Category 1, PLATE

Stopping distance and stopping time







## 28.4 D600\_L1600\_D1200



## Category 0, INTERCH

## Stopping distance and stopping time

*Continues on next page*

Category 0, ARM



Stopping distance and stopping time



Continues on next page

Category 0, PLATE



Stopping distance and stopping time



Continues on next page

Category 1, INTERCH



Stopping distance and stopping time



Continues on next page

Category 1, ARM



Stopping distance and stopping time



Continues on next page

Category 1, PLATE



Stopping distance and stopping time



## 28.5 D600\_L2000\_D1000

## Category 0, INTERCH



## Stopping distance and stopping time



Continues on next page

Category 0, ARM

Stopping distance and stopping time





Continues on next page



Category 0, PLATE



Stopping distance and stopping time



Continues on next page

Category 1, INTERCH



Stopping distance and stopping time



Continues on next page

Category 1, ARM



Stopping distance and stopping time



Continues on next page

Category 1, PLATE



Stopping distance and stopping time



## 28.6 D600\_L2000\_D1200



## Category 0, INTERCH

## Stopping distance and stopping time

*Continues on next page*

Category 0, ARM



Stopping distance and stopping time



Continues on next page

Category 0, PLATE



Stopping distance and stopping time



Continues on next page

Category 1, INTERCH

Stopping distance and stopping time





Continues on next page



Category 1, ARM



Stopping distance and stopping time



Continues on next page

Category 1, PLATE

Stopping distance and stopping time





# 29 IRBP K

## 29.1 K1000\_D1200

### Category 0, INTERCH

#### Stopping distance and stopping time



*Continues on next page*



# 29 IRBP K

## 29.1 K1000\_D1200

Continued

### Category 0, PLATE



#### Stopping distance and stopping time



Continues on next page

Category 1, INTERCH



Stopping distance and stopping time



Continues on next page

Category 1, PLATE



Stopping distance and stopping time



29.2 K1000\_D1400

Category 0, INTERCH



Stopping distance and stopping time



Continues on next page

Category 0, PLATE

Stopping distance and stopping time





Continues on next page



Category 1, INTERCH



Stopping distance and stopping time



Continues on next page

Category 1, PLATE



Stopping distance and stopping time



29.3 K300\_D1000

Category 0, INTERCH



Stopping distance and stopping time



Continues on next page

Category 0, PLATE



Stopping distance and stopping time



Continues on next page

Category 1, INTERCH



Stopping distance and stopping time



Continues on next page

Category 1, PLATE



Stopping distance and stopping time



29.4 K300\_D1200

Category 0, INTERCH



Stopping distance and stopping time



Continues on next page

Category 0, PLATE

Stopping distance and stopping time





Continues on next page



Category 1, INTERCH



Stopping distance and stopping time



Continues on next page

Category 1, PLATE



Stopping distance and stopping time



29.5 K600\_D1200

Category 0, INTERCH



Stopping distance and stopping time



Continues on next page

Category 0, PLATE



Stopping distance and stopping time



Continues on next page

Category 1, INTERCH



Stopping distance and stopping time



Continues on next page

Category 1, PLATE



Stopping distance and stopping time



29.6 K600\_D1400

Category 0, INTERCH



Stopping distance and stopping time



Continues on next page

Category 0, PLATE

Stopping distance and stopping time





Continues on next page



Category 1, INTERCH



Stopping distance and stopping time



Continues on next page

Category 1, PLATE

Stopping distance and stopping time





# 30 IRBP L

## 30.1 L1000

### Category 0, PLATE



#### Stopping distance and stopping time



*Continues on next page*

Category 1, PLATE



Stopping distance and stopping time



## 30.2 L2000

## Category 0, PLATE



## Stopping distance and stopping time



Continues on next page

Category 1, PLATE



Stopping distance and stopping time



## 30.3 L300



## Category 0, PLATE

## Stopping distance and stopping time

*Continues on next page*

Category 1, PLATE

Stopping distance and stopping time







## 30.4 L5000



## Category 0, PLATE

## Stopping distance and stopping time

*Continues on next page*

Category 1, PLATE



Stopping distance and stopping time



30.5 L600

Category 0, PLATE



Stopping distance and stopping time



Continues on next page

Category 1, PLATE

Stopping distance and stopping time





# 31 IRBP R

## 31.1 R1000\_L1600\_D1000

### Category 0, INTERCH

#### Stopping distance and stopping time



*Continues on next page*



# 31 IRBP R

## 31.1 R1000\_L1600\_D1000

Continued

### Category 0, PLATE



#### Stopping distance and stopping time



Continues on next page

Category 1, INTERCH

Stopping distance and stopping time



Continues on next page



# 31 IRBP R

## 31.1 R1000\_L1600\_D1000

Continued

### Category 1, PLATE

#### Stopping distance and stopping time







## 31.2 R1000\_L1600\_D1200

## Category 0, INTERCH

## Stopping distance and stopping time

*Continues on next page*



# 31 IRBP R

## 31.2 R1000\_L1600\_D1200

Continued

### Category 0, PLATE



#### Stopping distance and stopping time



Continues on next page

Category 1, INTERCH



Stopping distance and stopping time



Continues on next page

Category 1, PLATE



Stopping distance and stopping time



## 31.3 R1000\_L2000\_D1000



## Category 0, INTERCH

## Stopping distance and stopping time

*Continues on next page*

Category 0, PLATE



Stopping distance and stopping time



Continues on next page

Category 1, INTERCH



Stopping distance and stopping time



Continues on next page

Category 1, PLATE

Stopping distance and stopping time







## 31.4 R1000\_L2000\_D1200



## Category 0, INTERCH

## Stopping distance and stopping time

*Continues on next page*

Category 0, PLATE



Stopping distance and stopping time



Continues on next page

Category 1, INTERCH



Stopping distance and stopping time



Continues on next page

Category 1, PLATE



Stopping distance and stopping time



## 31.5 R300\_L1250\_D1000



## Category 0, INTERCH

## Stopping distance and stopping time

*Continues on next page*

Category 0, PLATE



Stopping distance and stopping time



Continues on next page

Category 1, INTERCH



Stopping distance and stopping time



Continues on next page

Category 1, PLATE

Stopping distance and stopping time







## 31.6 R300\_L1600\_D1000

## Category 0, INTERCH



## Stopping distance and stopping time



Continues on next page

Category 0, PLATE



Stopping distance and stopping time



Continues on next page

Category 1, INTERCH



Stopping distance and stopping time



Continues on next page

Category 1, PLATE



Stopping distance and stopping time



## 31.7 R600\_L1600\_D1000



## Category 0, INTERCH

## Stopping distance and stopping time

*Continues on next page*

Category 0, PLATE



Stopping distance and stopping time



Continues on next page

Category 1, INTERCH



Stopping distance and stopping time



Continues on next page

Category 1, PLATE

Stopping distance and stopping time







## 31.8 R600\_L1600\_D1200

## Category 0, INTERCH



## Stopping distance and stopping time



Continues on next page

Category 0, PLATE



Stopping distance and stopping time



Continues on next page

Category 1, INTERCH



Stopping distance and stopping time



Continues on next page

Category 1, PLATE



Stopping distance and stopping time



## 31.9 R600\_L2000\_D1000

## Category 0, INTERCH



## Stopping distance and stopping time



Continues on next page

Category 0, PLATE



Stopping distance and stopping time



Continues on next page

Category 1, INTERCH



Stopping distance and stopping time



Continues on next page

Category 1, PLATE

Stopping distance and stopping time







31.10 R600\_L2000\_D1200

Category 0, INTERCH



Stopping distance and stopping time



Continues on next page

Category 0, PLATE



Stopping distance and stopping time



Continues on next page

Category 1, INTERCH



Stopping distance and stopping time



Continues on next page

Category 1, PLATE

Stopping distance and stopping time



# Index

## A

AccSet, 13

## E

extension zone concept, 14

extension zone limits, 14

## L

limitations, 15

load, 14

## S

speed, 14

stopping distance, 14

stopping time, 14

## W

wcp, 14







**ABB AB**

**Robotics & Discrete Automation**

S-721 68 VÄSTERÅS, Sweden

Telephone +46 10-732 50 00

**ABB AS**

**Robotics & Discrete Automation**

Nordlysvegen 7, N-4340 BRYNE, Norway

Box 265, N-4349 BRYNE, Norway

Telephone: +47 22 87 2000

**ABB Engineering (Shanghai) Ltd.**

Robotics & Discrete Automation

No. 4528 Kangxin Highway

PuDong New District

SHANGHAI 201319, China

Telephone: +86 21 6105 6666

**ABB Inc.**

**Robotics & Discrete Automation**

1250 Brown Road

Auburn Hills, MI 48326

USA

Telephone: +1 248 391 9000

**[abb.com/robotics](http://abb.com/robotics)**